



GreenSpace Downlight G4

DN293B 1xDLED-3000 PSU WH

GreenSpace Downlight G4, 22 W, Beam angle 60 to 120°, Finger-protected

GreenSpace Gen4 is the new LED downlight with high efficacy (95~ 100lm/W) delivering substantial energy saving. It offers diverse configurations within 600~2,000lm. GreenSpace Gen4 could apply to shopping mall, retail store and office application with different variants . The lifetime is 50,000 hours (L70 @ 25C)

Product data

General Information	
Lamp family code	LED26 [LED module 2600 lm]
Light source replaceable	No
Number of gear units	1 unit
CE mark	CE mark
ENEC mark	-
Glow-wire test	Temperature 650 °C, duration 30 s
Light Technical	
Number of light sources	1
Light source color	830 warm white
Optic type	Beam angle 60 to 120°
Optical cover type	Transparent bowl with white cover
Luminaire light beam spread	90°
Operating and Electrical	
Input Voltage	220-240 V

Power Consumption	22 W
Power Factor (Fraction)	0.9
Temperature	
Ambient temperature range	-20 to +40 °C
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Constant light output	Yes
Mechanical and Housing	
Housing Material	Aluminum
Reflector material	Polycarbonate
Optic material	Polycarbonate

GreenSpace Downlight G4

Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%
Product Data	
Full product code	911401567321

Order product name	DN293B 1xDLED-3000 PSU WH
Order code	911401567321
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	911401567321
Full product name	DN293B 1xDLED-3000 PSU WH

Dimensional drawing

