

# GreenSpace Downlight G4

## DN290B 1xDLED-3000 PSU ALU CAU

GreenSpace Downlight G4, 6.5 W, Beam angle 60 to 120°, Finger-protected

GreenSpace Gen4 is the new LED downlight with high efficacy (95~ 100lm/W) delivering substantial energy saving. It offers diverse configurations within 600~2,000lm. GreenSpace Gen4 could apply to shopping mall, retail store and office application with different variants . The lifetime is 50,000 hours (L70 @ 25C)

### Product data

| General Information | |
|---|---|
| **Light source replaceable** | No |
| **Number of gear units** | 1 unit |
| **CE mark** | CE mark |
| **ENEC mark** | - |
| **Glow-wire test** | Temperature 650 °C, duration 30 s |

| Light Technical | |
|---|---|
| **Number of light sources** | 1 |
| **Light source color** | 830 warm white |
| **Optic type** | Beam angle 60 to 120° |
| **Optical cover type** | Transparent bowl with white cover |
| **Luminaire light beam spread** | 90° |

| Operating and Electrical | |
|---|---|
| **Input Voltage** | 220-240 V |
| **Power Consumption** | 6.5 W |
| **Power Factor (Fraction)** | 0.9 |
| **Cable** | Cord with plug SAA 3-pole |

| Temperature | |
|---|---|
| **Ambient temperature range** | -20 to +40 °C |

| Controls and Dimming | |
|---|---|
| **Dimmable** | No |
| **Driver/power unit/transformer** | Power supply unit (On/Off) |
| **Constant light output** | Yes |

| Mechanical and Housing | |
|---|---|
| **Housing Material** | Aluminum |
| **Reflector material** | Polycarbonate |
| **Optic material** | Polycarbonate |

# GreenSpace Downlight G4

| Approval and Application | |
|---|---|
| **Ingress protection code** | IP20 [Finger-protected] |
| **Mech. impact protection code** | IK02 [0.2 J standard] |


| Initial Performance (IEC Compliant) | |
|---|---|
| **Luminous flux tolerance** | +/-10% |
| **Power consumption tolerance** | +/-10% |


| Product Data | |
|---|---|
| **Order product name** | DN290B 1xDLED-3000 PSU ALU CAU |

| | |
|---|---|
| **Full product name** | DN290B 1xDLED-3000 PSU ALU CAU |
| **Full product code** | 871016330039999 |
| **Order code** | 911401568221 |
| **Material Nr. (12NC)** | 911401568221 |
| **Local order code** | DN290B7W3KFA |
| **Numerator - Quantity Per Pack** | 1 |
| **EAN/UPC - Product/Case** | 8710163300399 |
| **Numerator - Packs per outer box** | 36 |

## Dimensional drawing


| Dimension 灯具尺寸 | A (mm) | B (mm) |
|---|---|---|
| DN290B 1xDLED / ALU | 95 / 99 | Φ 122 |
| DN291B 1xDLED / ALU | 105 /109 | Φ 167 |
| DN292B 1xDLED / ALU | 114 / 118 | Φ 218 |
| DN293B 1xDLED / ALU | 114 / 118 | Φ 218 |






| Dimension 灯具尺寸 | A (mm) | B (mm) |
|---|---|---|
| DN290B 1xDLED / ALU | 95 / 99 | Φ 122 |
| DN291B 1xDLED / ALU | 105 /109 | Φ 167 |
| DN292B 1xDLED / ALU | 114 / 118 | Φ 218 |
| DN293B 1xDLED / ALU | 114 / 118 | Φ 218 |


© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.