



# GreenSpace Downlight G4

## DN292B 1xDLED-3000 PSD WH CAU

GreenSpace Downlight G4, 16 W, Beam angle 60 to 120°, Finger-protected

GreenSpace Gen4 is the new LED downlight with high efficacy (95~ 100lm/W) delivering substantial energy saving. It offers diverse configurations within 600~2,000lm. GreenSpace Gen4 could apply to shopping mall, retail store and office application with different variants . The lifetime is 50,000 hours (L70 @ 25C)

### Product data

|                             |                                   |
|-----------------------------|-----------------------------------|
| General Information         |                                   |
| Light source replaceable    | No                                |
| Number of gear units        | 1 unit                            |
| CE mark                     | CE mark                           |
| ENEC mark                   | -                                 |
| Glow-wire test              | Temperature 650 °C, duration 30 s |
| Light Technical             |                                   |
| Number of light sources     | 1                                 |
| Light source color          | 830 warm white                    |
| Optic type                  | Beam angle 60 to 120°             |
| Optical cover type          | Transparent bowl with white cover |
| Luminaire light beam spread | 90°                               |
| Operating and Electrical    |                                   |
| Input Voltage               | 220-240 V                         |
| Power Consumption           | 16 W                              |

|                               |                                       |
|-------------------------------|---------------------------------------|
| Power Factor (Fraction)       | 0.9                                   |
| Cable                         | Cord with plug SAA 3-pole             |
| Temperature                   |                                       |
| Ambient temperature range     | -20 to +40 °C                         |
| Controls and Dimming          |                                       |
| Driver/power unit/transformer | Power supply unit with DALI interface |
| Constant light output         | No                                    |
| Mechanical and Housing        |                                       |
| Housing Material              | Aluminum                              |
| Reflector material            | Polycarbonate                         |
| Optic material                | Polycarbonate                         |
| Approval and Application      |                                       |
| Ingress protection code       | IP20 [Finger-protected]               |

GreenSpace Downlight G4

|                                     |                               |
|-------------------------------------|-------------------------------|
| Mech. impact protection code        | IK02 [0.2 J standard]         |
| Initial Performance (IEC Compliant) |                               |
| Luminous flux tolerance             | +/-10%                        |
| Power consumption tolerance         | +/-10%                        |
| Product Data                        |                               |
| Order product name                  | DN292B 1xDLED-3000 PSD WH CAU |
| Full product name                   | DN292B 1xDLED-3000 PSD WH CAU |

|                                 |                 |
|---------------------------------|-----------------|
| Full product code               | 871016330049899 |
| Order code                      | 911401569221    |
| Material Nr. (12NC)             | 911401569221    |
| Local order code                | DN292B15W3KDW   |
| Numerator - Quantity Per Pack   | 1               |
| EAN/UPC - Product/Case          | 8710163300498   |
| Numerator - Packs per outer box | 12              |

Dimensional drawing

