



GreenSpace Downlight G4

DN292B 1xDLED-4000 PSD WH CAU

GreenSpace Downlight G4, 16 W, 4000 K, Beam angle 60 to 120°, Finger-protected

GreenSpace Gen4 is the new LED downlight with high efficacy (95~ 100lm/W) delivering substantial energy saving. It offers diverse configurations within 600~2,000lm. GreenSpace Gen4 could apply to shopping mall, retail store and office application with different variants . The lifetime is 50,000 hours (L70 @ 25C)

Product data

General Information	
Light source replaceable	No
Number of gear units	1 unit
CE mark	CE mark
ENEC mark	-
Glow-wire test	Temperature 650 °C, duration 30 s
Light Technical	
Correlated Color Temperature (Nom)	4000 K
Number of light sources	1
Light source color	840 neutral white
Optic type	Beam angle 60 to 120°
Optical cover type	Transparent bowl with white cover
Luminaire light beam spread	90°
Operating and Electrical	
Input Voltage	220-240 V

Power Consumption	16 W
Power Factor (Fraction)	0.9
Cable	Cord with plug SAA 3-pole
Temperature	
Ambient temperature range	-20 to +40 °C
Controls and Dimming	
Driver/power unit/transformer	Power supply unit with DALI interface
Constant light output	No
Mechanical and Housing	
Housing Material	Aluminum
Reflector material	Polycarbonate
Optic material	Polycarbonate

GreenSpace Downlight G4

Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%
Product Data	
Order product name	DN292B 1xDLED-4000 PSD WH CAU

Full product name	DN292B 1xDLED-4000 PSD WH CAU
Full product code	871016330050499
Order code	911401569321
Material Nr. (12NC)	911401569321
Local order code	DN292B15W4KDW
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8710163300504
Numerator - Packs per outer box	12

Dimensional drawing

