



GreenSpace Downlight G4

DN293B 1xDLED-4000 PSD WH CAU

GreenSpace Downlight G4, 22 W, 4000 K, Beam angle 60 to 120°, Finger-protected

GreenSpace Gen4 is the new LED downlight with high efficacy (95~ 100lm/W) delivering substantial energy saving. It offers diverse configurations within 600~2,000lm. GreenSpace Gen4 could apply to shopping mall, retail store and office application with different variants . The lifetime is 50,000 hours (L70 @ 25C)

Product data

General Information		Power Consumption	
Light source replaceable	No	Power Factor (Fraction)	0.9
Number of gear units	1 unit	Cable	Cord with plug SAA 3-pole
CE mark	CE mark	Temperature	
ENEC mark	-	Ambient temperature range	-20 to +40 °C
Glow-wire test	Temperature 650 °C, duration 30 s	Controls and Dimming	
Light Technical		Driver/power unit/transformer	Power supply unit with DALI interface
Correlated Color Temperature (Nom)	4000 K	Constant light output	No
Number of light sources	1	Mechanical and Housing	
Light source color	840 neutral white	Housing Material	Aluminum
Optic type	Beam angle 60 to 120°	Reflector material	Polycarbonate
Optical cover type	Transparent bowl with white cover	Optic material	Polycarbonate
Luminaire light beam spread	90°		
Operating and Electrical			
Input Voltage	220-240 V		

GreenSpace Downlight G4

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Product Data

Order product name	DN293B 1xDLED-4000 PSD WH CAU
--------------------	-------------------------------

Full product name	DN293B 1xDLED-4000 PSD WH CAU
Full product code	871016330054299
Order code	911401569721
Material Nr. (12NC)	911401569721
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8710163300542
Numerator - Packs per outer box	12

Dimensional drawing

