



# GreenSpace Downlight G4

## DN293B 1xDLED-4000 PSU WH WP

GreenSpace Downlight G4, 22 W, 4000 K, Beam angle 60 to 120°, Finger-protected

GreenSpace Gen4 is the new LED downlight with high efficacy (95~ 100lm/W) delivering substantial energy saving. It offers diverse configurations within 600~2,000lm. GreenSpace Gen4 could apply to shopping mall, retail store and office application with different variants . The lifetime is 50,000 hours (L70 @ 25C)

### Product data

|                                    |                                   |                                      |  |
|------------------------------------|-----------------------------------|--------------------------------------|--|
| <b>General Information</b>         |                                   | <b>Power Consumption</b>             |  |
| Light source replaceable           | No                                | 22 W                                 |  |
| Number of gear units               | 1 unit                            | <b>Power Factor (Fraction)</b>       |  |
| CE mark                            | CE mark                           | 0.9                                  |  |
| ENEC mark                          | -                                 | <b>Temperature</b>                   |  |
| Glow-wire test                     | Temperature 650 °C, duration 30 s | <b>Ambient temperature range</b>     |  |
| <b>Light Technical</b>             |                                   | -20 to +40 °C                        |  |
| Correlated Color Temperature (Nom) | 4000 K                            | <b>Controls and Dimming</b>          |  |
| Number of light sources            | 1                                 | <b>Dimmable</b>                      |  |
| Light source color                 | 840 neutral white                 | No                                   |  |
| Optic type                         | Beam angle 60 to 120°             | <b>Driver/power unit/transformer</b> |  |
| Optical cover type                 | Transparent bowl with white cover | Power supply unit (On/Off)           |  |
| Luminaire light beam spread        | 90°                               | <b>Constant light output</b>         |  |
| <b>Operating and Electrical</b>    |                                   | Yes                                  |  |
| Input Voltage                      | 220-240 V                         | <b>Mechanical and Housing</b>        |  |
|                                    |                                   | <b>Housing Material</b>              |  |
|                                    |                                   | Aluminum                             |  |
|                                    |                                   | <b>Reflector material</b>            |  |
|                                    |                                   | Polycarbonate                        |  |
|                                    |                                   | <b>Optic material</b>                |  |
|                                    |                                   | Polycarbonate                        |  |

# GreenSpace Downlight G4

|                                     |                              |
|-------------------------------------|------------------------------|
| Approval and Application            |                              |
| Ingress protection code             | IP20 [Finger-protected]      |
| Mech. impact protection code        | IK02 [0.2 J standard]        |
| Initial Performance (IEC Compliant) |                              |
| Luminous flux tolerance             | +/-10%                       |
| Power consumption tolerance         | +/-10%                       |
| Product Data                        |                              |
| Order product name                  | DN293B 1xDLED-4000 PSU WH WP |

|                                 |                              |
|---------------------------------|------------------------------|
| Full product name               | DN293B 1xDLED-4000 PSU WH WP |
| Full product code               | 911401578921                 |
| Order code                      | 01578921                     |
| Material Nr. (12NC)             | 911401578921                 |
| Numerator - Quantity Per Pack   | 1                            |
| Numerator - Packs per outer box | 12                           |

## Dimensional drawing

