



# GreenSpace Downlight G4

## DN293B 1xDLED-4000 PSU ALU WP

GreenSpace Downlight G4, 22 W, 4000 K, Beam angle 60 to 120°, Finger-protected

GreenSpace Gen4 is the new LED downlight with high efficacy (95~ 100lm/W) delivering substantial energy saving. It offers diverse configurations within 600~2,000lm. GreenSpace Gen4 could apply to shopping mall, retail store and office application with different variants . The lifetime is 50,000 hours (L70 @ 25C)

### Product data

<b>General Information</b>		<b>Power Consumption</b>	
Light source replaceable	No	22 W	
Number of gear units	1 unit	<b>Power Factor (Fraction)</b>	
CE mark	CE mark	0.9	
ENEC mark	-	<b>Temperature</b>	
Glow-wire test	Temperature 650 °C, duration 30 s	<b>Ambient temperature range</b>	
<b>Light Technical</b>		-20 to +40 °C	
Correlated Color Temperature (Nom)	4000 K	<b>Controls and Dimming</b>	
Number of light sources	1	<b>Dimmable</b>	
Light source color	840 neutral white	No	
Optic type	Beam angle 60 to 120°	<b>Driver/power unit/transformer</b>	
Optical cover type	Transparent bowl with white cover	Power supply unit (On/Off)	
Luminaire light beam spread	90°	<b>Constant light output</b>	
<b>Operating and Electrical</b>		Yes	
Input Voltage	220-240 V	<b>Mechanical and Housing</b>	
		<b>Housing Material</b>	
		Aluminum	
		<b>Reflector material</b>	
		Polycarbonate	
		<b>Optic material</b>	
		Polycarbonate	

# GreenSpace Downlight G4

Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%
Product Data	
Full product code	911401580021

Order product name	DN293B 1xDLED-4000 PSU ALU WP
Order code	911401580021
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	911401580021
Full product name	DN293B 1xDLED-4000 PSU ALU WP

## Dimensional drawing

