



GreenSpace Downlight G4

DN291B 1xDLED-3000 PSU WH CAU

GreenSpace Downlight G4, 11.6 W, Beam angle 60 to 120°,
Finger-protected

GreenSpace Gen4 is the new LED downlight with high efficacy (95~ 100lm/W) delivering substantial energy saving. It offers diverse configurations within 600~2,000lm. GreenSpace Gen4 could apply to shopping mall, retail store and office application with different variants . The lifetime is 50,000 hours (L70 @ 25C)

Product data

General Information		Power Factor (Fraction)		0.9
Light source replaceable	No	Cable		Cord with plug SAA 3-pole
Number of gear units	1 unit	Temperature		
CE mark	CE mark	Ambient temperature range		-20 to +40 °C
ENEC mark	-	Controls and Dimming		
Glow-wire test	Temperature 650 °C, duration 30 s	Dimmable		No
Light Technical		Driver/power unit/transformer		Power supply unit (On/Off)
Number of light sources	1	Constant light output		Yes
Light source color	830 warm white	Mechanical and Housing		
Optic type	Beam angle 60 to 120°	Housing Material		Aluminum
Optical cover type	Transparent bowl with white cover	Reflector material		Polycarbonate
Luminaire light beam spread	90°	Optic material		Polycarbonate
Operating and Electrical				
Input Voltage	220-240 V			
Power Consumption	11.6 W			

GreenSpace Downlight G4

Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%
Product Data	
Order product name	DN291B 1xDLED-3000 PSU WH CAU

Full product name	DN291B 1xDLED-3000 PSU WH CAU
Full product code	871016330055999
Order code	911401580621
Material Nr. (12NC)	911401580621
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8710163300559
Numerator - Packs per outer box	24

Dimensional drawing

