PHILIPS

Lighting



# GreenSpace G5

## DN392B LED16/830 PSU D200 WH CAU

GreenSpace G5, 14.5 W, 1500 lm, 3000 K, High-gloss high reflectance, Matte, Finger-protected

GreenSpace Gen5 is a new LED downlight range combining light efficiency and comfort with product diversity and system compatibility

### Product data

| General Information | |
|---|---|
| **Light source replaceable** | No |
| **Number of gear units** | 1 unit |
| **Driver included** | Yes |
| **Light source engine type** | LED |
| **CE mark** | CE mark |
| **Warranty period** | 3 years |
| **Flammability mark** | For mounting on normally flammable surfaces |
| **Glow-wire test** | Temperature 650 °C, duration 30 s |

| Light Technical | |
|---|---|
| **Luminous Flux** | 1,500 lm |
| **Correlated Color Temperature (Nom)** | 3000 K |
| **Luminous Efficacy (rated) (Nom)** | 103 lm/W |
| **Color rendering index (CRI)** | >80 |
| **Beam angle of light source** | 92 degree(s) |
| **Light source color** | 830 warm white |
| **Optic type** | High-gloss high reflectance |
| **Optical cover type** | Transparent bowl with white cover |
| **Luminaire light beam spread** | 80° |

| Operating and Electrical | |
|---|---|
| **Input Voltage** | 220-240 V |
| **Line Frequency** | 50 or 60 Hz |
| **Inrush current** | 2.2 A |
| **Inrush time** | 0.045 ms |
| **Power Consumption** | 14.5 W |
| **Power Factor (Fraction)** | 0.95 |
| **Connection** | Push-in connector 6-pole |
| **Cable** | Cable with plug |
| **Number of products on MCB of 16 A type B** | 48 |

| Temperature | |
|---|---|
| **Ambient temperature range** | -20 to +40 °C |

| Controls and Dimming | |
|---|---|
| **Dimmable** | No |
| **Control interface** | - |
| **Constant light output** | No |

# GreenSpace G5

| Mechanical and Housing | |
|---|---|
| **Housing Material** | Aluminum die cast |
| **Reflector material** | Polycarbonate |
| **Optic material** | Polycarbonate |
| **Optical cover material** | Polycarbonate |
| **Housing Color** | Black and white |
| **Optical cover finish** | Matte |
| **Overall length** | 0 mm |
| **Overall width** | 0 mm |
| **Overall height** | 108 mm |
| **Overall diameter** | 216 mm |
| **Dimensions (Height x Width x Depth)** | 108 x 0 x 0 mm |

| Approval and Application | |
|---|---|
| **Ingress protection code** | IP20 [Finger-protected] |
| **Mech. impact protection code** | IK02 [0.2 J standard] |
| **Protection class IEC** | Safety class I |


| Initial Performance (IEC Compliant) | |
|---|---|
| **Luminous flux tolerance** | +/-10% |
| **Initial chromaticity** | (0.44,0.403) SDCM<5 |
| **Power consumption tolerance** | +/-10% |

| Over Time Performance (IEC Compliant) | |
|---|---|
| **Driver failure rate at 5000 h** | 0.16 % |
| **Median useful life L70B50** | 50,000 hour(s) |
| **Median useful life L80B50** | 43,000 hour(s) |
| **Median useful life L90B50** | 20,000 hour(s) |

| Application Conditions | |
|---|---|
| **Maximum dim level** | Not applicable |

| Product Data | |
|---|---|
| **Order product name** | DN392B LED16/830 PSU D200 WH CAU |
| **Full product name** | DN392B LED16/830 PSU D200 WH CAU |
| **Full product code** | 911401583241 |
| **Order code** | 911401583241 |
| **Material Nr. (12NC)** | 911401583241 |
| **Numerator - Quantity Per Pack** | 1 |
| **Numerator - Packs per outer box** | 1 |

## Dimensional drawing




© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.