



# GreenPerform Hygeia

## CR418B LED80/Y

GreenPerform Hygeia, 80 W, Amber, 4800 lm, Wide beam, Wire-protected

Customers operating highly hygienic facilities require, easy-to-clean, dust-free luminaires that meet all lighting requirements and norms. The New Hygeia with a IP40 and compliance to 1,000 – 100,000 class cleanroom makes It a good choice. The new Hygeia CR308 has a streamlined shape that minimizes dust gathering and disturbed airflow. The cleanroom luminaire uses the latest Philips LED Line platform to provide most value for money. This means extremely low operational cost over the total lifetime of the luminaire, and so an excellent financial return on investment.

### Product data

General Information		Operating and Electrical	
Lamp family code	LED49S [LED module, system flux 4900 lm]	Luminous Efficacy (rated) (Nom)	60 lm/W
Light source replaceable	No	Color rendering index (CRI)	80
Number of gear units	1 unit	Beam angle of light source	120 degree(s)
Gear	-	Light source color	Amber
Driver included	Yes	Optic type	Wide beam
CE mark	-	Optical cover type	Polycarbonate bowl/cover frosted
Warranty period	3 years	Luminaire light beam spread	110°
Flammability mark	-		
ENEC mark	-		
Glow-wire test	Temperature 650 °C, duration 30 s	Input Voltage	220-240 V
EU RoHS compliant	No	Line Frequency	50 to 60 Hz
		Inrush current	20 A
		Inrush time	0.25 ms
		Power Consumption	80 W
		Power Factor (Fraction)	0.9
		Connection	Internal connector
Light Technical			
Luminous Flux	4,800 lm		
Correlated Color Temperature (Nom)	-		

# GreenPerform Hygeia

Cable	-
Number of products on MCB of 16 A type B	24
<b>Temperature</b>	
Ambient temperature range	-25 to +35 °C
<b>Controls and Dimming</b>	
Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Constant light output	No
<b>Mechanical and Housing</b>	
Housing Material	Steel
Reflector material	-
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	-
Housing Color	White
Optical cover finish	Frosted
Overall length	1,198 mm
Overall width	148 mm
Overall height	65 mm
Dimensions (Height x Width x Depth)	65 x 148 x 1198 mm
<b>Approval and Application</b>	
Ingress protection code	IP40 [Wire-protected]
Mech. impact protection code	IK03 [0.3 J]

Protection class IEC	Safety class I
<b>Initial Performance (IEC Compliant)</b>	
Luminous flux tolerance	+/-7.5%
Initial chromaticity	-
Power consumption tolerance	+/-10%
<b>Over Time Performance (IEC Compliant)</b>	
Driver failure rate at 5000 h	1 %
Median useful life L70B50	50,000 hour(s)
Median useful life L80B50	35,000 hour(s)
Median useful life L90B50	25,000 hour(s)
<b>Application Conditions</b>	
Suitable for random switching	No
<b>Product Data</b>	
Order product name	CR418B LED80/Y
Full product name	CR418B LED80/Y
Full product code	911401591901
Order code	911401591901
Material Nr. (12NC)	911401591901
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

## Dimensional drawing



