

UNIflood

BCP260 24xLED-HP/RD 24V MB DMX

UNIflood, 42 W, Red, Medium beam, Safety class III

UNIflood is a mono-color LED floodlighting fixture designed for a wide range of architectural floodlighting applications. Available in a choice of whites and other light colors, it offers reliable quality and outstanding performance. The fixture's advanced LED technology creates a vivid and harmonious ambience at night whilst also saving energy.

Product data

General Information	
Lamp family code	LED-HP [LED High Power]
Lighting Technology	LED
Embedded control	Dynamic DMX
Flammability mark	For mounting on normally flammable surfaces

Light Technical	
Number of light sources	24
Light source color	Red
Optic type outdoor	Medium beam

Operating and Electrical	
Input Voltage	24 V
Power Consumption	42 W


Temperature	
Ambient temperature range	-20 to +50 °C

Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Protection class IEC	Safety class III

Product Data	
Order product name	BCP260 24xLED-HP/RD 24V MB DMX
Full product name	BCP260 24xLED-HP/RD 24V MB DMX
Full product code	911401600271
Order code	911401600271
Material Nr. (12NC)	911401600271
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

UNIflood

Dimensional drawing



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.