



UNiflood

BCP260 24xLED-HP/RD 24V NB DMX

UNiflood, 42 W, Red, Narrow beam, Safety class III

UNiflood is a mono-color LED floodlighting fixture designed for a wide range of architectural floodlighting applications. Available in a choice of whites and other light colors, it offers reliable quality and outstanding performance. The fixture's advanced LED technology creates a vivid and harmonious ambience at night whilst also saving energy.

Product data

| General Information | |
|---------------------------|---|
| Lamp family code | LED-HP [LED High Power] |
| Lighting Technology | LED |
| Embedded control | Dynamic DMX |
| Flammability mark | For mounting on normally flammable surfaces |
| Light Technical | |
| Number of light sources | 24 |
| Light source color | Red |
| Optic type outdoor | Narrow beam |
| Operating and Electrical | |
| Input Voltage | 24 V |
| Power Consumption | 42 W |
| Temperature | |
| Ambient temperature range | -20 to +50 °C |

| Approval and Application | |
|---------------------------------|--|
| Ingress protection code | IP65 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK06 [1 J] |
| Protection class IEC | Safety class III |
| Product Data | |
| Full product code | 911401600281 |
| Order product name | BCP260 24xLED-HP/RD 24V NB DMX |
| Order code | 911401600281 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 1 |
| Material Nr. (12NC) | 911401600281 |
| Full product name | BCP260 24xLED-HP/RD 24V NB DMX |

Dimensional drawing

