



UNiflood

BCP260 24xLED-HP/AM 24V MB DMX

UNiflood, 42 W, Amber, Medium beam, Safety class III

UNiflood is a mono-color LED floodlighting fixture designed for a wide range of architectural floodlighting applications. Available in a choice of whites and other light colors, it offers reliable quality and outstanding performance. The fixture's advanced LED technology creates a vivid and harmonious ambience at night whilst also saving energy.

Product data

General Information	
Lamp family code	LED-HP [LED High Power]
Lighting Technology	LED
Embedded control	Dynamic DMX
Flammability mark	For mounting on normally flammable surfaces
Light Technical	
Number of light sources	24
Light source color	Amber
Optic type outdoor	Medium beam
Operating and Electrical	
Input Voltage	24 V
Power Consumption	42 W
Temperature	
Ambient temperature range	-20 to +50 °C

Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Protection class IEC	Safety class III
Product Data	
Full product code	911401600302
Order product name	BCP260 24xLED-HP/AM 24V MB DMX
Order code	911401600302
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401600302
Full product name	BCP260 24xLED-HP/AM 24V MB DMX

Dimensional drawing

