



UNIflood

BCP260 24xLED-HP/WW-2700 24V NB

UNIflood, 42 W, Warm white, Narrow beam, Safety class III

UNIflood is a mono-color LED floodlighting fixture designed for a wide range of architectural floodlighting applications. Available in a choice of whites and other light colors, it offers reliable quality and outstanding performance. The fixture's advanced LED technology creates a vivid and harmonious ambience at night whilst also saving energy.

Product data

General Information	
Lamp family code	LED-HP [LED High Power]
Lighting Technology	LED
Embedded control	-
Flammability mark	For mounting on normally flammable surfaces
Light Technical	
Correlated Color Temperature (Nom)	2700 K
Number of light sources	24
Light source color	Warm white
Optic type outdoor	Narrow beam
Operating and Electrical	
Input Voltage	24 V
Power Consumption	42 W
Temperature	
Ambient temperature range	-20 to +50 °C

Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Protection class IEC	Safety class III
Product Data	
Order product name	BCP260 24xLED-HP/WW-2700 24V NB
Full product name	BCP260 24xLED-HP/WW-2700 24V NB
Full product code	911401600521
Order code	911401600521
Material Nr. (12NC)	911401600521
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

Dimensional drawing

