



# Tango G2 LED

## BVP281 LED88/NW 80W 220-240V SWB

Tango G2 LED, Safety class I

Tango G2 LED is a general purpose LED flood lighting luminaire for various lighting applications, such as area lighting, bill-board, façade, industry area, recreational sports and other general applications. The Tango G2 LED flood light incorporates LED light source, optical system, heat sink and driver into one compact housing. Its specially designed heat sink incorporates aesthetics and functionality to ensure reliability and long lifetime. Tango G2 LED takes advantage of LED technology which provides energy savings and a longer lifetime, bringing area lighting into a new era.

### Product data

<b>General Information</b>	
Driver included	Yes
Lighting Technology	LED
CE mark	CE mark
<b>Light Technical</b>	
Color rendering index (CRI)	80
<b>Operating and Electrical</b>	
Input Voltage	220-240 V
Line Frequency	50 to 60 Hz
<b>Temperature</b>	
Ambient temperature range	-40 to +50 °C
<b>Mechanical and Housing</b>	
Housing Material	Aluminum extruded
Optic material	Polycarbonate

Optical cover material	Polycarbonate
<b>Approval and Application</b>	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Protection class IEC	Safety class I
<b>Product Data</b>	
Order product name	BVP281 LED88/NW 80W 220-240V SWB
Full product name	BVP281 LED88/NW 80W 220-240V SWB
Full product code	911401634102
Order code	911401634102
Material Nr. (12NC)	911401634102
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	6947939171842
Numerator - Packs per outer box	1
EAN/UPC - Case	6947939171842

## Tango G2 LED

---

### Dimensional drawing

