



SportsStar-BVP621/BVP622/EVP62 2

EVP622 IP66 960W 380-415V DMX

LED - Power supply unit - Dynamix DMX

Philips SportsStar LED Floodlight sets the standard in high quality optical distribution with high performance and low light pollution (or effective light control). From Sports to Area Lighting, our system, including the high masts needed, projects the light exactly where it should be going. Choose the right illumination levels for any given setting with Philips SportsStar LED Floodlight.

Product data

General Information	
Number of gear units	2 units
Driver/power unit/transformer	Power supply unit
Driver included	Yes
Control interface	Dynamix DMX
Connection	Flying leads/wires
Cable	Cable 1.5 m without plug
Protection class IEC	Safety class I
Warranty period	3 years
Constant light output	No
Light source engine type	LED

Operating and Electrical	
Input Voltage	347-480 V
Input Frequency	50 or 60 Hz
Power Factor (Min)	0.95
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Housing Material	Aluminum die-cast
Fixation material	Aluminum
Overall length	595 mm
Overall width	517 mm

Datasheet, 2017, September 28 data subject to change


SportsStar-BVP621/BVP622/EVP622


Overall height	142 mm
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. Impact protection code	IK08 [5 J vandal-protected]
Surge Protection (Common/Differential)	Luminaire surge protection level until 10 kV differential
	mode and 10 kV common mode
Initial Performance (IEC Complian	t)
Initial input power	960 W
Power consumption tolerance	+/-10%
Application Conditions	
Ambient temperature range	-40 to +55 °C


911401666003
EVP622 IP66 960W 380-415V DMX
911401666003
1
1
911401666003
19.000 kg



Dimensional drawing







SportsStar - BVP621/BVP622/EVP622

