



Essential Smartbright LED

BVP161 LED26/NW 30W 220-240V WB GREY

Essential Smartbright LED, 2600 lm, 30 W, 740 neutral white, Safety class I

Philips Essential SmartBright LED Floodlight not only ensures savings on initial capital, but also delivers reliable operational savings.

Product data

General Information		Cable	
Driver included	Yes	Cable 0.3 m without plug	
Lighting Technology	LED	Temperature	
CE mark	CE mark	Ambient temperature range	
Light Technical		-40 to +45 °C	
Luminous Flux	2,600 lm	Controls and Dimming	
Correlated Color Temperature (Nom)	4000 K	Dimmable	
Luminous Efficacy (rated) (Nom)	86.67 lm/W	No	
Color rendering index (CRI)	>70	Control interface	
Light source color	740 neutral white	-	
Optical cover type	Micro-lens optic in polycarbonate cover, wide	Mechanical and Housing	
Operating and Electrical		Housing Material	
Input Voltage	220-240 V	Aluminum die cast	
Line Frequency	50 to 60 Hz	Optic material	
Power Consumption	30 W	Polycarbonate	
Power Factor (Fraction)	0.9	Optical cover material	
Connection	Flying leads/wires	Polycarbonate	
		Housing Color	
		Grey	
		Overall length	
		193.2 mm	
		Overall width	
		142.5 mm	
		Overall height	
		33.8 mm	
		Dimensions (Height x Width x Depth)	
		34 x 143 x 193 mm	

Essential Smartbright LED

Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Protection class IEC	Safety class I
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%
Product Data	
Order product name	BVP161 LED26/NW 30W 220-240V WB GREY

Full product name	BVP161 LED26/NW 30W 220-240V WB GREY
Full product code	871016330428199
Order code	911401805398
Material Nr. (12NC)	911401805398
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8710163304281
Numerator - Packs per outer box	16
EAN/UPC - Case	8710163304342

Dimensional drawing

