



Xtend LED

RC115B LED35S/840 PSD W30L120

Xtend LED, 840 neutral white

Xtend LED is the new generation of linear design troffer with good illuminating uniformity and high efficiency

Product data

General Information		Power Factor (Fraction)		0.9
Lamp family code	LED22 [LED module 2200 lm]	Temperature		
Light source replaceable	No	Ambient temperature range		-20 to +40 °C
Number of gear units	1 unit	Controls and Dimming		
Driver included	Yes	Driver/power unit/transformer		Power supply unit with DALI interface
Glow-wire test	Temperature 650 °C, duration 30 s	Constant light output		No
CE mark	CE mark	Mechanical and Housing		
ENEC mark	-	Housing Material		Steel
Light Technical		Reflector material		Steel
Correlated Color Temperature (Nom)	4000 K	Optic material		Polymethyl methacrylate
Color rendering index (CRI)	80	Housing Color		White
Number of light sources	1	Approval and Application		
Light source color	840 neutral white	Ingress protection code		IP20 [Finger-protected]
Optic type	Beam angle 60 to 120°	Mech. impact protection code		IK02 [0.2 J standard]
Optical cover type	Transparent bowl with white cover	Protection class IEC		Safety class I
Luminaire light beam spread	110° x 110°	Initial Performance (IEC Compliant)		
Operating and Electrical		Luminous flux tolerance		+/-10%
Input Voltage	220-240 V			
Power Consumption	36.5 W			

Power consumption tolerance	+/-10%
-----------------------------	--------

Product Data	
Order product name	RC115B LED35S/840 PSD W30L120
Full product name	RC115B LED35S/840 PSD W30L120
Full product code	911401830399

Order code	911401830399
Material Nr. (12NC)	911401830399
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2

Dimensional drawing

