



Greenperform Batten

BN208C LED60/CW L1500 PSD ACF EN

Greenperform Batten, 51 W, 6500 K, Wide beam

GreenPerform Batten BN208C Dali is a high quality LED batten that delivers significant energy savings of up to 50% comparing to conventional T8 battens. BN208X incorporates the reliable structure, long lifetime LED lighting, and the global standard ZigBee control system, to achieve an easy-to-use networked solution. In the mean time, it helps to further increase energy saving maximum to 80% with daylight harvest and occupancy sensor.

Warnings and Safety

- The product is IPX0 & as such is not protected against water ingress & as such we strongly recommend that the environment in which the luminaire is to be installed is suitably checked
- If the above advice is not taken and the luminaires are subject to water ingress, Philips / Signify cannot guarantee safe failure & product warranty will become void

Product data

General Information		Color rendering index (CRI)	
Lamp family code	LED60S [LED Module, system flux 6000 lm]	Light source color	Cool white
Light source replaceable	No	Optic type	Wide beam
Number of gear units	1 unit	Optical cover type	Opal
Gear	-	Luminaire light beam spread	110°
Driver included	Yes	Operating and Electrical	
CE mark	CE mark	Input Voltage	220-240 V
Flammability mark	-	Line Frequency	50 to 60 Hz
ENEC mark	-	Power Consumption	51 W
Glow-wire test	Temperature 650 °C, duration 30 s	Power Factor (Fraction)	0.9
Light Technical		Connection	Screw connection block 3-pole
Correlated Color Temperature (Nom)	6500 K		

Greenperform Batten

Temperature	
Ambient temperature range	-20 to +40 °C
Controls and Dimming	
Dimmable	Yes
Driver/power unit/transformer	Power supply unit with DALI interface
Constant light output	Yes
Mechanical and Housing	
Housing Material	Steel
Optic material	Polycarbonate
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class I
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-7.5%

Initial chromaticity	-
Power consumption tolerance	+/-10%
Application Conditions	
Maximum dim level	1% (depends on dimmer, ELV)
Product Data	
Order product name	BN208C LED60/CW L1500 PSD ACF EN
Full product name	BN208C LED60/CW L1500 PSD ACF EN
Full product code	911401831499
Order code	911401831499
Material Nr. (12NC)	911401831499
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

Dimensional drawing

-

