



SmartBright Lowbay

BY118P LED16/NW PSU

LED module, system flux 1700 lm, Neutral white, Power supply unit (On/Off)

A perfect LED replacement to CFL Lowbay systems, allowing you to brighten up factories, supermarkets, retail shops, and sports recreational spaces the smarter way.


Product data

General Information		Operating and Electrical	
Lamp family code	LED17S [LED module, system flux 1700 lm]	Input Voltage	220-240 V
Light source replaceable	No	Line Frequency	50 to 60 Hz
Number of gear units	1 unit	Power Consumption	20 W
Gear	-	Power Factor (Fraction)	0.9
Driver included	Yes	Connection	-
CE mark	CE mark	Temperature	
Flammability mark	-	Ambient temperature range	-20 to +40 °C
ENEC mark	-	Controls and Dimming	
Glow-wire test	Temperature 650 °C, duration 30 s	Dimmable	No
Light Technical		Driver/power unit/transformer	Power supply unit (On/Off)
Correlated Color Temperature (Nom)	4000 K	Constant light output	Yes
Color rendering index (CRI)	80	Mechanical and Housing	
Light source color	Neutral white	Housing Material	Polycarbonate
Optic type	Wide beam	Reflector material	Polycarbonate
Optical cover type	Micro-lens optic in polycarbonate cover	Optic material	Polycarbonate
Luminaire light beam spread	90°		

Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class I
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-7.5%
Initial chromaticity	-
Power consumption tolerance	+/-10%
Application Conditions	
Maximum dim level	Not applicable

Product Data	
Full product code	871016330777000
Order product name	BY118P LED16/NW PSU
Order code	911401833299
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401833299
Full product name	BY118P LED16/NW PSU
EAN/UPC - Case	8710163307770
EAN/UPC - Product/Case	8710163307770

Dimensional drawing



Type	Q	W
BY118P LED16	24	180
BY118P LED21	24	180
BY118P LED24	24	180

