



SmartBright Panel

RC099V LED36S/865 W60L60 PCV GM

SmartBright Panel, 865 cool daylight

SmartBright Panel is the most affordable LED panel delivering comfortable light with excellent uniformity

Product data

| General Information | |
|------------------------------------|-----------------------------------|
| Light source replaceable | No |
| Number of gear units | 1 unit |
| Driver included | Yes |
| Glow-wire test | Temperature 650 °C, duration 30 s |
| CE mark | CE mark |
| ENEC mark | - |
| Light Technical | |
| Correlated Color Temperature (Nom) | 6500 K |
| Color rendering index (CRI) | 80 |
| Number of light sources | 12 |
| Light source color | 865 cool daylight |
| Optic type | Beam angle 60 to 120° |
| Optical cover type | Transparent bowl with white cover |
| Luminaire light beam spread | 110° x 110° |
| Operating and Electrical | |
| Input Voltage | 220-240 V |
| Power Consumption | 34 W |
| Power Factor (Fraction) | 0.9 |

| Controls and Dimming | |
|-------------------------------------|---------------------------------|
| Dimmable | No |
| Driver/power unit/transformer | Power supply unit (On/Off) |
| Constant light output | Yes |
| Mechanical and Housing | |
| Housing Material | Steel |
| Reflector material | Steel |
| Optic material | Polycarbonate |
| Housing Color | White |
| Approval and Application | |
| Ingress protection code | IP20 [Finger-protected] |
| Mech. impact protection code | IK02 [0.2 J standard] |
| Protection class IEC | Safety class I |
| Initial Performance (IEC Compliant) | |
| Luminous flux tolerance | +/-10% |
| Power consumption tolerance | +/-10% |
| Product Data | |
| Order product name | RC099V LED36S/865 W60L60 PCV GM |

SmartBright Panel

| | |
|---------------------|---------------------------------|
| Full product name | RC099V LED36S/865 W60L60 PCV GM |
| Full product code | 911401836099 |
| Order code | 911401836099 |
| Material Nr. (12NC) | 911401836099 |

| | |
|---------------------------------|---|
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 2 |

Dimensional drawing

