



Vandalite Waterproof

BCW098 LED40/CW PSD L1200

Vandalite Waterproof, 38 W, 6500 K, 120°

Mini Vandalite LED is the perfect all-night luminaire for industrial corridors, security lighting, garages and residential areas. LED-based, it reduces cost with low energy consumption and low maintenance because of LEDs' high reliablity and long service life. It can be either ceiling or wall-mounted, and the translucent bowl provides excellent distribution of low-level lighting for the surroundings. Robust with vandal-resistant construction, Mini Vandalite LED is suitable for both outdoor and indoor applications.

Product data

| General Information | |
|------------------------------------|--|
| Lamp family code | LED40S [LED module, system flux 4000 lm] |
| Light source replaceable | No |
| Number of gear units | 1 unit |
| Gear | - |
| Driver included | Yes |
| Glow-wire test | Temperature 650 °C, duration 30 s |
| Flammability mark | - |
| CE mark | CE mark |
| ENEC mark | - |
| | |
| Light Technical | |
| Correlated Color Temperature (Nom) | 6500 K |
| Color rendering index (CRI) | 85 |
| Light source color | Cool white |
| Optic type | Wide beam |
| Optical cover type | Opal |
| | |

| Luminaire light beam spread | 120° |
|-------------------------------|---------------------------------------|
| | |
| Operating and Electrical | |
| Input Voltage | 220-240 V |
| Line Frequency | 50 to 60 Hz |
| Power Consumption | 38 W |
| Power Factor (Fraction) | 0.9 |
| Connection | - |
| Cable | Cable 0.5 m with cable connector |
| | |
| Temperature | |
| Ambient temperature range | -20 to +45 °C |
| | |
| Controls and Dimming | |
| Dimmable | Yes |
| Driver/power unit/transformer | Power supply unit with DALI interface |
| Constant light output | Yes |

Datasheet, 2023, September 4 data subject to change

Vandalite Waterproof

| Mechanical and Housing | | |
|-------------------------------------|--|--|
| Housing Material | Polyester | |
| Optic material | Polycarbonate | |
| | | |
| Approval and Application | | |
| Ingress protection code | IP65 [Dust penetration-protected, jet-proof] | |
| Mech. impact protection code | IK10 [20 J vandal-resistant] | |
| Protection class IEC | Safety class I | |
| | | |
| Initial Performance (IEC Compliant) | | |
| Luminous flux tolerance | +/-7.5% | |
| Initial chromaticity | - | |
| Power consumption tolerance | +/-10% | |
| | | |
| Application Conditions | | |
| Maximum dim level | 1% (depends on dimmer, ELV) | |
| | | |

| Product Data | |
|---------------------------------|---------------------------|
| Order product name | BCW098 LED40/CW PSD L1200 |
| Full product name | BCW098 LED40/CW PSD L1200 |
| Full product code | 911401840099 |
| Order code | 911401840099 |
| Material Nr. (12NC) | 911401840099 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 8710163308005 |
| Numerator - Packs per outer box | 1 |
| EAN/UPC - Case | 8710163308005 |
| | · |

Dimensional drawing





