



# SmartBright LED Batten

## BN012C LED20/CW L1200

SmartBright LED Batten, 21 W, 6500 K

SmartBright LED Batten G2 is an affordable replacement for T5 and T8 battens in indirect lighting solutions, such as pelmet or cove lighting. The product comes in a variety of lengths, and an excellent lifetime of 30,000 hours. The product also comes with a plug in the packaging, so is easy for installation.

### Product data

General Information		Power Factor (Fraction)	
Light source replaceable	No	0.8	
Driver included	Yes	Temperature	
CE mark	CE mark	Ambient temperature range	-20 to +35 °C
Flammability mark	-	Controls and Dimming	
ENEC mark	-	Dimmable	No
Light Technical		Driver/power unit/transformer	Power supply unit (On/Off)
Correlated Color Temperature (Nom)	6500 K	Mechanical and Housing	
Color rendering index (CRI)	80	Housing Material	Polycarbonate
Optic type	-	Optic material	Polycarbonate
Luminaire light beam spread	110°	Housing Color	White
Operating and Electrical		Approval and Application	
Input Voltage	220-240 V	Ingress protection code	IP20 [Finger-protected]
Line Frequency	50 to 60 Hz	Mech. impact protection code	IK02 [0.2 J standard]
Power Consumption	21 W		

# SmartBright LED Batten

Initial Performance (IEC Compliant)		Full product code	
Luminous flux tolerance	+/-10%	Order code	01840299
Power consumption tolerance	+/-10%	Material Nr. (12NC)	911401840299
Application Conditions		Numerator - Quantity Per Pack	1
Maximum dim level	Not applicable	EAN/UPC - Product/Case	8710163301259
Product Data		Numerator - Packs per outer box	25
Order product name	BN012C LED20/CW L1200	EAN/UPC - Case	8710163301334
Full product name	BN012C LED20/CW L1200		

## Dimensional drawing

