



OneSpace luminous ceiling prefab

LP710P ONESPACE PREFAB L2860W1733 4000K

OneSpace luminous ceiling prefab panel, length 2860 mm, width 1733 mm, light color 4000 K

Many business customers want a lighting solution that recalls the feeling of natural daylight, creating a calm and peaceful environment. They want great functional lighting that feels as good as it looks. Philips OneSpace luminous ceiling prefab is an impressive ultra-thin and compact standard unit with an excellent uniform light distribution. It also helps improve the acoustics in a room and meets the most stringent fire safety standards. The result is a ceiling unit that produces an amazing light effect while the light source remains hidden from view. With its minimalistic design, this slim, compact unit will blend in perfectly with any interior.

Product data

General Information		Operating and Electrical	
Number of light sources	1 pc	Input Voltage	220 to 240 V
Light source color	840 neutral white	Input Frequency	50 to 60 Hz
Light source replaceable	No	Control signal voltage	0-16 V DC DALI
Driver/power unit/transformer	Power supply unit with DALI interface	Controls and Dimming	
Driver included	Yes	Dimmable	Yes
Connection	Screw connection block 3-pole		
Protection class IEC	Safety class I		
Ready-to-install	Ready-to-install		
Flammability mark	-		
Type description	OneSpace luminous ceiling prefab panel, length 2860 mm, width 1733 mm, light color 4000 K		
CE mark	CE mark		
ENEC mark	ENEC mark		
UL mark	UL mark		
Unified glare rating CEN	Not applicable		

OneSpace luminous ceiling prefab

Mechanical and Housing

Housing Material	Aluminum
Gear tray material	Steel
Color	Black

Approval and Application

Ingress protection code	IP00 [No protection]
Mech. impact protection code	IK00 [No protection]

Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	12500 lm
Initial LED luminaire efficacy	66 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>85
Initial input power	190 W
Power consumption tolerance	+/-10%

Application Conditions

Ambient temperature range	+5 to +35 °C
Maximum dim level	10%
Suitable for random switching	No

Product Data

Full product code	871869607036999
Order product name	LP710P ONESPACE PREFAB L2860W1733 4000K
EAN/UPC - Product	8718696070369
Order code	9120000000417
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	9120000000417
Net Weight (Piece)	54.000 kg

