



Arc

SGP618 CDM-T150W SIP I EB CUR S ALU KC 6

Arc 80, MASTERColour CDM-T, 150 W, Electronic, Safety class I, Curved, Symmetrical, Aluminum, Spigot for diameter 60 mm

With its streamlined shape, Arc has been specially designed to create a distinctive, modern and functional luminaire range that is suitable for both standard renovation applications and new area developments. Rather than forming an obtrusive presence, it harmonizes with its architectural surroundings. Arc's attractive price/performance ratio makes it highly suitable for large-scale use.

Product data

General Information		Line Frequency		50 to 60 Hz
Lamp family code	CDM-T [MASTERColour CDM-T]	Power Consumption		150 W
Cap-Base	G12 [G12]	Temperature		
Light source replaceable	Yes	Ambient temperature range		-30 to +35 °C
Number of gear units	1 unit	Controls and Dimming		
Gear	EB [Electronic]	Dimmable		Yes
Product family code	SGP618 [Arc 80]	Mechanical and Housing		
Glow-wire test	Temperature 650 °C, duration 5 s	Housing Material		Aluminum
CE mark	Yes	Reflector material		Aluminum
ENEC mark	ENEC mark	Housing Color		Aluminum
Light Technical		Mounting device		Spigot for diameter 60 mm
Standard tilt angle posttop	0°	Optical cover shape		Curved
Number of light sources	1	Optical cover finish		Clear
Optic type outdoor	Symmetrical			
Operating and Electrical				
Input Voltage	230 to 240 V			

Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Protection class IEC	Safety class I

Product Data	
Order product name	SGP618 CDM-T150W SIP I EB CUR S ALU KC 6
Full product name	SGP618 CDM-T150W SIP I EB CUR S ALU KC 6
Full product code	871794317983100

Order code	912300022876
Material Nr. (12NC)	912300022876
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8717943179831
Numerator - Packs per outer box	1
EAN/UPC - Case	8717943179831

Dimensional drawing

