



# Arc

## SGP618 PL-T/4P42W SIP I HFP CUR S ALU KC

Arc 80, MASTER PL-T 4 Pin, 42 W, HF Performer, Safety class I, Curved, Symmetrical, Aluminum

With its streamlined shape, Arc has been specially designed to create a distinctive, modern and functional luminaire range that is suitable for both standard renovation applications and new area developments. Rather than forming an obtrusive presence, it harmonizes with its architectural surroundings. Arc's attractive price/performance ratio makes it highly suitable for large-scale use.

#### **Product data**

PL-T/4P [MASTER PL-T 4 Pin]
GX24Q-4 [GX24q-4]
Yes
1 unit
HFP [HF Performer]
SGP618 [Arc 80]
Temperature 650 °C, duration 5 s
Yes
ENEC mark
0°
1
Symmetrical
230 to 240 V

Line Frequency	50 to 60 Hz
Power Consumption	42 W
Temperature	
Ambient temperature range	−30 to +35 °C
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Housing Material	Aluminum
Reflector material	Aluminum
Housing Color	Aluminum
Optical cover shape	Curved
Optical cover finish	Clear
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]

Datasheet, 2023, September 4 data subject to change

#### Arc

Mech. impact protection code	IK08 [5 J vandal-protected]
Protection class IEC	Safety class I
Product Data	
Order product name	SGP618 PL-T/4P42W SIP I HFP CUR S ALU KC
Full product name	SGP618 PL-T/4P42W SIP I HFP CUR S ALU KC
Full product code	871794317990900
Order code	912300022883

Material Nr. (12NC)	912300022883
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8717943179909
Numerator - Packs per outer box	1
EAN/UPC - Case	8717943179909

### Dimensional drawing







