



Arc

SGP618 PL-T/4P57W SIP I HFP CUR S ALU KC

Arc 80, MASTER PL-T 4 Pin, 57 W, HF Performer, Safety class I, Curved, Symmetrical, Aluminum

With its streamlined shape, Arc has been specially designed to create a distinctive, modern and functional luminaire range that is suitable for both standard renovation applications and new area developments. Rather than forming an obtrusive presence, it harmonizes with its architectural surroundings. Arc's attractive price/performance ratio makes it highly suitable for large-scale use.

Product data

General Information		Line Frequency		50 to 60 Hz
Lamp family code	PL-T/4P [MASTER PL-T 4 Pin]	Power Consumption		57 W
Cap-Base	GX24Q-5 [GX24q-5]	Temperature		
Light source replaceable	Yes	Ambient temperature range		-30 to +35 °C
Number of gear units	1 unit	Controls and Dimming		
Gear	HFP [HF Performer]	Dimmable		Yes
Product family code	SGP618 [Arc 80]	Mechanical and Housing		
Glow-wire test	Temperature 650 °C, duration 5 s	Housing Material		Aluminum
CE mark	Yes	Reflector material		Aluminum
ENEC mark	ENEC mark	Housing Color		Aluminum
Light Technical		Optical cover shape		Curved
Standard tilt angle posttop	0°	Optical cover finish		Clear
Number of light sources	1	Approval and Application		
Optic type outdoor	Symmetrical	Ingress protection code		IP66 [Dust penetration-protected, jet-proof]
Operating and Electrical				
Input Voltage	230 to 240 V			

Mech. impact protection code	IK08 [5 J vandal-protected]
Protection class IEC	Safety class I
Product Data	
Order product name	SGP618 PL-T/4P57W SIP I HFP CUR S ALU KC
Full product name	SGP618 PL-T/4P57W SIP I HFP CUR S ALU KC
Full product code	871794317991600
Order code	912300022884

Material Nr. (12NC)	912300022884
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8717943179916
Numerator - Packs per outer box	1
EAN/UPC - Case	8717943179916

Dimensional drawing

