



FlowLine driver units

EGB330 6K SH D9 MDD

FLOWLINE DRIVER, Safety class I, Fuse included, Mains outlet socket and 2 DALI sockets

It is important to limit tunnel closures for maintenance as much as possible. To this end, we have separated the FlowLine driver from the LED unit. In doing so, we have obtained the optimal thermal properties and lifetime expectancy to reduce maintenance. The option to locate the drivers outside the driving envelope (remote) further reduces the need for closures.

Product data

General Information	
Driver included	Yes
Product family code	EGB330 [FLOWLINE DRIVER]
CE mark	Yes
ENEC mark	-
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Connection	Mains outlet socket and 2 DALI sockets
Temperature	
Ambient temperature range	-25 to +40 °C
Controls and Dimming	
Dimmable	Yes
Driver/power unit/transformer	Power supply unit with DALI interface

Mechanical and Housing	
Overall length	395 mm
Overall width	225 mm
Overall height	845 mm
Dimensions (Height x Width x Depth)	845 x 225 x 395 mm
Material	Stainless steel
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Protection class IEC	Safety class I
Product Data	
Full product code	871794318179700
Order product name	EGB330 6K SH D9 MDD
Order code	912300022919
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

FlowLine driver units

Material Nr. (12NC)	912300022919
Full product name	EGB330 6K SH D9 MDD
EAN/UPC - Case	8717943181797

EAN/UPC - Product/Case	8717943181797
------------------------	---------------

Dimensional drawing

