



Arc

SGP618 CPO-TW140W/728 S CUR AL ALU KC 60

Arc 80, MASTER CosmoWhite CPO-TW, 140 W, 728 warm white, Symmetrical, Curved, Aluminium, Spigot for diameter 60 mm

With its streamlined shape, Arc has been specially designed to create a distinctive, modern and functional luminaire range that is suitable for both standard renovation applications and new area developments. Rather than forming an obtrusive presence, it harmonizes with its architectural surroundings. Arc's attractive price/performance ratio makes it highly suitable for large-scale use.

Product data

General Information		Operating and Electrical	
Lamp family code	CPO-TW [MASTER CosmoWhite CPO-TW]	Input Voltage	230 to 240 V
Cap base	PGZ12 [PGZ12]	Line Frequency	50 to 60 Hz
Light source replaceable	Yes	Power Consumption	140 W
Number of gear units	Unit	Temperature	
Gear	EB [Electronic]	Ambient temperature range	-30 to +35 °C
Product family code	SGP618 [Arc 80]	Controls and Dimming	
CE mark	Yes	Dimmable	Yes
ENEC mark	ENEC mark	Mechanical and Housing	
Glow-wire test	Temperature 650 °C, duration 5 s	Housing material	Aluminium
Light Technical		Reflector material	Aluminium
Standard tilt angle post-top	0°	Housing Colour	Aluminium
Correlated Colour Temperature	2800 K	Mounting device	Spigot for diameter 60 mm
Light source colour	728 warm white	Optical cover/lens shape	Curved
Optic type outdoor	Symmetrical		

Optical cover/lens finish	Clear
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Protection class IEC	Safety class I
Product Data	
Order product name	SGP618 CPO-TW140W/728 S CUR AL ALU KC 60
Full product name	SGP618 CPO-TW140W/728 S CUR AL ALU KC 60

Full EOC	871794318416300
Order code	18416300
Material no. (12 NC)	912300022983
Local order code	.
SAP numerator – quantity per pack	1
EAN/UPC – Product/Case	8717943184163
Numerator – packs per outer box	1
EAN/UPC – Case	8717943184163

Dimensional drawing

