


Stela+ gen2 Round

BPP610 1450/NW PSU WRN CLO 60P L20

STELA ROUND GEN2, LED XP-G2, Power supply unit (On/Off), Wide road optic for S-class, Constant light output, Post-top for diameter 60 mm

Stela Round is at the forefront of LED technology in street lighting. The REVOLED cooling and light distribution concept enables tremendous energy savings and a corresponding reduction in CO2 emissions, whilst meeting current lighting standards. Excellent thermal management of the LEDs ensures a very long lifetime, eliminating the need for lamp replacement and resulting in a very attractive Total Cost of Ownership. The introduction of the latest-generation LED and programmable drivers and the possibility of employing Constant Light Output (CLO) in gen2 enable a further reduction in power consumption.

Product data

General Information	
Lamp family code	XP-G2 [LED XP-G2]
Light source replaceable	No
Number of gear units	1 unit
Driver included	Yes
Light source engine type	LED
Product family code	BPP610 [STELA ROUND GEN2]
Lighting Technology	LED
Embedded control	Constant light output
CE mark	Yes
Warranty period	5 years
Flammability mark	-
ENEC mark	-

EU RoHS compliant	Yes

Light Technical	
Upward light output ratio	0
Luminous Flux	1,305 lumen
Standard tilt angle posttop	0°
Standard tilt angle side entry	-
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	109 lm/W
Color rendering index (CRI)	≥70
Number of light sources	12
Light source color	Neutral white
Optical cover type	Polymethyl methacrylate bowl/cover
Luminaire light beam spread	154° x 118°

Stela+ gen2 Round

Optic type outdoor	Wide road optic for S-class

Operating and Electrical

Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Initial CLO power consumption	12 W
Average CLO power consumption	12 W
End CLO power consumption	12 W
Inrush current	65 A
Inrush time	100 ms
Power Consumption	12 W
Power Factor (Fraction)	0.86
Connection	Screw connection with pug and socket
Cable	-
Number of products on MCB of 16 A type B	1

Temperature

Ambient temperature range	-20 to +35 °C

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Constant light output	Yes

Mechanical and Housing

Housing Material	Aluminum
Reflector material	-
Optic material	Acrylate
Optical cover material	Polymethyl methacrylate
Fixation material	Aluminum
Housing Color	Grey
Mounting device	Post-top for diameter 60 mm
Optical cover shape	Curved
Optical cover finish	Clear

Overall height	195 mm
Overall diameter	600 mm
Effective projected area	0.065 m²

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK10 [20 J vandal-resistant]
Surge Protection (Common/Differential)	Luminaire surge protection level until 6 kV differential mode and 6 kV common mode
Protection class IEC	Safety class I
Photobiological risk	Photobiological risk group 1 @200mm to EN62778

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-7%
Initial chromaticity	(0.380, 0.380) SDCM <7
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2


Over Time Performance (IEC Compliant)

Driver failure rate at 5000 h	0.5 %

Product Data

Full product code	871794322827000
Order product name	BPP610 1450/NW PSU WRN CLO 60P L20
Order code	912300025955
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912300025955
Full product name	BPP610 1450/NW PSU WRN CLO 60P L20
EAN/UPC - Case	8717943228270
EAN/UPC - Product/Case	8717943228270

Dimensional drawing



Stela+ gen2 Round

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.