


Stela+ gen2 Round

BPP611 36x /NW PSU II WRN AL GR SRG10 76

STELA-ROUND AREA GEN2, LED XP-G2, LED, Neutral white, Power supply unit (On/Off), 220 to 240 V, 50 to 60 Hz, Safety class I, Wide road optic for S-class, Polymethyl methacrylate bowl/cover, Grey, Luminaire surge protection level until 10 kV differential mode and 10 kV common mode, Post-top for diameter 76 mm

Stela Round is at the forefront of LED technology in street lighting. The REVOLED cooling and light distribution concept enables tremendous energy savings and a corresponding reduction in CO2 emissions, whilst meeting current lighting standards. Excellent thermal management of the LEDs ensures a very long lifetime, eliminating the need for lamp replacement and resulting in a very attractive Total Cost of Ownership. The introduction of the latest-generation LED and programmable drivers and the possibility of employing Constant Light Output (CLO) in gen2 enable a further reduction in power consumption.

Product data

General Information	
Lamp family code	XP-G2 [LED XP-G2]
Light source replaceable	No
Number of gear units	1 unit
Driver included	Yes
Light source engine type	LED
Product family code	BPP611 [STELA-ROUND AREA GEN2]
Lighting Technology	LED
CE mark	Yes
Warranty period	5 years

Flammability mark	-
ENEC mark	-
EU RoHS compliant	Yes

Light Technical	
Upward light output ratio	0
Luminous Flux	5,000 lumen
Standard tilt angle posttop	0°
Standard tilt angle side entry	-
Correlated Color Temperature (Nom)	4000 K

Stela+ gen2 Round

Luminous Efficacy (rated) (Nom)	113 lm/W
Color rendering index (CRI)	≥70
Light source color	Neutral white
Optical cover type	Polymethyl methacrylate bowl/cover
Luminaire light beam spread	154° x 118°
Optic type outdoor	Wide road optic for S-class

Operating and Electrical

Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Inrush current	80 A
Inrush time	150 ms
Power Consumption	44 W
Power Factor (Fraction)	0.9
Connection	Screw connection with pug and socket
Cable	-
Number of products on MCB of 16 A type B	1

Temperature

Ambient temperature range	-20 to +35 °C

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Constant light output	No

Mechanical and Housing

Housing Material	Aluminum
Reflector material	-
Optic material	Acrylate
Optical cover material	Polymethyl methacrylate
Fixation material	Aluminum
Housing Color	Grey
Mounting device	Post-top for diameter 76 mm
Optical cover shape	Curved
Optical cover finish	Clear
Overall height	195 mm
Overall diameter	600 mm
Effective projected area	0.065 m²

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK10 [20 J vandal-resistant]
Surge Protection (Common/Differential)	Luminaire surge protection level until 10 kV differential mode and 10 kV common mode
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-7%
Initial chromaticity	(0.380, 0.380) SDCM <7
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2


Over Time Performance (IEC Compliant)

Driver failure rate at 5000 h	0.5 %

Product Data

Full product code	871794323706700
Order product name	BPP611 36x /NW PSU II WRN AL GR SRG10 76
Order code	912300026477
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912300026477
Full product name	BPP611 36x /NW PSU II WRN AL GR SRG10 76
EAN/UPC - Case	8717943237067
EAN/UPC - Product/Case	8717943237067

Dimensional drawing



Stela+ gen2 Round

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.