



## **Vaya Linear MP**



Vaya Linear MP, RGB, 50°, 1.2 m (4 ft), CE

Vaya Linear MP, RGB, 50°, 1.2 m (4 ft), CE

Vaya Linear MP is a reliable and cost-effective LED lighting fixture designed for fixed or dynamic colourful lighting effects. Offering a choice of wide or elliptical beams, Vaya Linear MP is ideal for wall washing and grazing applications. Integrated power and unified power and data connectors make installation fast, easy and reliable.

## **Product data**

General information	
Lamp family code	LED-HB [ LED High Brightness]
Beam angle of light source	50 °
Light source colour	Red, green and blue
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	GC [ Clear glass]
CE mark	CE mark
UL mark	No
CQC mark	-
Lifetime to 70% luminous flux	60000 h
PSE mark	PSE mark
Operating and electrical	
Input Voltage	100 to 277 V
Input frequency	50 to 60 Hz
Controls and dimming	
Dimmable	Yes

Mechanical and housing	
Housing material	Extruded aluminium
Optic material	Glass
Optical cover/lens material	Tempered glass
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Length	1210 mm
Colour	Dark Grey
Approval and application	
Ingress protection code	IP66 [ Dust penetration-protected, jet-
	proof]
Energy Efficiency Class	G
Mech. impact protection code	IK06 [1J]
Vibration standard	Complies with ANSI C136.31
Vibration rating	Complies with ANSI C136.31
	1081408
Initial performance (IEC compliant)	
Initial luminous flux (system flux)	1906 lm

Datasheet, 2022, September 15 data subject to change


## Vaya Linear MP

Initial LED luminaire efficacy	35.1 lm/W
Init. Corr. Colour Temperature	- K
Initial input power	60 W
Over time performance (IEC compliant)	)
Lumen Maintenance 50% at 25 °C Calculated	100000
Lumen Maintenance 50% at 25 °C Reported	36000
Lumen Maintenance 50% at 40 °C Calculated	63000
Lumen Maintenance 50% at 40 °C Reported	36000
Lumen Maintenance 70% at 25 °C Calculated	100000
Lumen Maintenance 70% at 25 °C Reported	36000
Lumen Maintenance 70% at 40 °C Calculated	29000
Lumen Maintenance 70% at 40 °C Reported	29000
Application conditions	
Ambient temperature range	-40 to +40 °C


Product data	
Full product code	871829162557599
Order product name	BCP424 50 RGB L1210 CE
EAN/UPC – product	8718291625575
Order code	316-000011-02
Local order code	BCP424RGBL1210
SAP numerator – quantity per pack	1
Numerator – packs per outer box	4
SAP material	912400130058
Net Weight (Piece)	3.850 kg
Commercial Code	316-000011-02
Catalogue number description	Vaya Linear MP, RGB, 50°, 1.2 m (4 ft), CE



## Dimensional drawing



BCP424 50 RGB L1210 CE



BCP424 50 RGB L1210 CE



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.