



Lighting

PHILIPS

Vaya Linear MP

BCP425 50 5000 L1210 CE CQC

Vaya Linear MP is a reliable and cost-effective LED lighting fixture designed for fixed or dynamic colourful lighting effects. Offering a choice of wide or elliptical beams, Vaya Linear MP is ideal for wall washing and grazing applications. Integrated power and unified power and data connectors make installation fast, easy and reliable.

Product data

General Information	
Lamp family code	LED-HB [LED High Brightness]
Beam angle of light source	50 °
Lamp colour code	Cool white
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	GC [Clear glass]
CE mark	CE mark
UL mark	No
CQC mark	CQC-mark
Lifetime to 70% luminous flux	60000 h
PSE mark	No
Operating and Electrical	
Input voltage	100 to 277 V
Input frequency	50 to 60 Hz
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Housing material	Aluminum extruded

Optic material	Glass	
Optical cover/lens material	Tempered glass	
Optical cover/lens shape	Flat	
Optical cover/lens finish	Clear	
Length	1210 mm	
Colour	Dark Grey	
Approval and Application		
Ingress protection code	IP66 [Dust penetration-protected, jet-	
	proof]	
Mech. impact protection code	IK06 [1 J]	
Initial Performance (IEC Compliant)		
Initial luminous flux	3360 lm	
Lamp colour temperature	5000 K	
Initial input power	60 W	
Over Time Performance (IEC Compliant)		
Lumen Maintenance 70% at 25°C Calculated	100000	
Lumen Maintenance 70% at 25°C Reported	60000	
Lumen Maintenance 70% at 40°C Calculated 100000		
Lumen Maintenance 70% at 40°C Reported	60000	

Vaya Linear MP

Lumen Maintenance 80% at 25°C Reported	60000
Lumen Maintenance 80% at 40°C Calculated	100000
Lumen Maintenance 80% at 40°C Reported	60000
Lumen Maintenance 80% at 50°C Calculated	100000
Lumen Maintenance 90% at 25°C Calculated	62000
Lumen Maintenance 90% at 25°C Reported	60000
Lumen Maintenance 90% at 40°C Calculated	62000
Lumen Maintenance 90% at 40°C Reported	60000
Application Conditions	


-40 to +40 °C

Product Data	
Full product code	871829162613899
Order product name	BCP425 50 5000 L1210 CE CQC
EAN/UPC – product	8718291626138
Order code	912400130163
Numerator – quantity per pack	1
Numerator – packs per outer box	4
Material no. (12NC)	912400130163
Net weight (piece)	3.850 kg

IK 06

Ambient temperature range

Dimensional drawing





© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2019, May 2 - data subject to change