**PHILIPS** Lighting



# eW Burst Powercore gen2

# eW Burst Powercore gen2, 2700 K, 6° Native (no spread lens), Black housing, Landscape

eW Burst Powercore gen2, 2700 K, 6° Native (no spread lens), Black housing, Landscape

eW Burst Powercore gen2 is a high-output, exterior-rated LED lighting luminaire designed for accent and site lighting.;Architectural and Landscape versions deliver high-quality white light output in a warm 2,700 K and a neutral 4,000 K to support a range of uplighting, floodlighting and decorative lighting applications.

### **Product data**

General information		
Light source replaceable	No	
Driver included	Yes	
Optical cover/lens type	GT [ Tempered glass]	
Luminaire light beam spread	6°	
CE mark	CE mark	
UL mark	UL and cUL mark	
Operating and electrical		
Input Voltage	100 to 277 V	
Input frequency	50 to 60 Hz	
Controls and dimming		
Dimmable	Yes	

Mechanical and housing		
Colour	Black	
Colour	Black	
Approval and application		
Ingress protection code	IP66 [ Dust penetration-protected, jet-	
	proof]	
FCC mark	FCC Class A	
Initial performance (IEC compliant)		
Initial LED luminaire efficacy	64.7 lm/W	
Init. Corr. Colour Temperature	2700 K	
Init. Colour rendering index	81	
Initial input power	30 W	

## eW Burst Powercore gen2


Over time performance (IEC compliant)			
Lumen Maintenance 50% at 25 °C Calculated	100000		
Lumen Maintenance 50% at 25 °C Reported	51000		
Lumen Maintenance 50% at 50 °C Calculated	100000		
Lumen Maintenance 50% at 50 °C Reported	51000		
Lumen Maintenance 70% at 25 °C Calculated	84000		
Lumen Maintenance 70% at 25 °C Reported	51000		
Lumen Maintenance 70% at 50 °C Calculated	83000		
Lumen Maintenance 70% at 50 °C Reported	51000		
Lumen Maintenance 90% at 25 °C Calculated	28000		
Lumen Maintenance 90% at 25 °C Reported	28000		
Lumen Maintenance 90% at 50 °C Calculated	27000		
Lumen Maintenance 90% at 50 °C Reported	27000		
Application conditions			
Ambient temperature range	-40 to +50 °C		

Product data	
Full product code	871869921561399
Order product name	BCP463 G2 19xLED-HB/2700 HMA BK
EAN/UPC – product	8718699215613
Order code	523-000098-03
SAP numerator – quantity per pack	1
Numerator – packs per outer box	2
SAP material	912400133360
Net Weight (Piece)	3.470 kg
Commercial Code	523-000098-03
Catalogue number description	eW Burst Powercore gen2, 2700 K, 6°
	Native (no spread lens), Black housing,
	Landscape

#### Ambient temperature range

IP 66

### **Dimensional drawing**



BCP463 G2 19xLED-HB/2700 HMA BK



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2022, October 11 - data subject to change