



eW Burst Powercore gen2

eW Burst Powercore gen2, 4000 K, 6° Native (no spread lens), White housing, Architectural

eW Burst Powercore gen2, 4000 K, 6° Native (no spread lens), White housing, Architectural

eW Burst Powercore gen2 is a high-output, exterior-rated LED lighting luminaire designed for accent and site lighting. Architectural and Landscape versions deliver high-quality white light output in a warm 2,700 K and a neutral 4,000 K to support a range of uplighting, floodlighting and decorative lighting applications.

Product data

General information	
Luminaire light beam spread	6°
CE mark	CE mark
UL mark	UL and cUL mark
Operating and electrical	
Input Voltage	100 to 277 V
Input frequency	50 to 60 Hz
Mechanical and housing	
Colour	White
Approval and application	
Ingress protection code	IP60 [Dust penetration-protected]
Vibration standard	Complies with ANSI C136.31, 3G

FCC mark	FCC Class A
Vibration rating	Complies with ANSI C136.31, 3G
Initial performance (IEC compliant)	
Initial luminous flux (system flux)	2096 lm
Initial LED luminaire efficacy	74.6 lm/W
Init. Corr. Colour Temperature	4000 K
Init. Colour rendering index	81
Initial input power	30 W
Over time performance (IEC compliant)	
Lumen Maintenance 50% at 25 °C Calculated	100000
Lumen Maintenance 50% at 25 °C Reported	51000
Lumen Maintenance 50% at 50 °C Calculated	100000
Lumen Maintenance 50% at 50 °C Reported	51000

eW Burst Powercore gen2

Lumen Maintenance 70% at 25 °C Calculated	84000
Lumen Maintenance 70% at 25 °C Reported	51000
Lumen Maintenance 70% at 50 °C Calculated	83000
Lumen Maintenance 70% at 50 °C Reported	51000
Lumen Maintenance 90% at 25 °C Calculated	28000
Lumen Maintenance 90% at 25 °C Reported	28000
Lumen Maintenance 90% at 50 °C Calculated	27000
Lumen Maintenance 90% at 50 °C Reported	27000

Application conditions


Ambient temperature range	-40 to +50 °C
---------------------------	---------------

Product data

Full product code	871869921572999
-------------------	-----------------

Order product name	BCP463 G2 19xLED-HB/4000 WH
EAN/UPC – product	8718699215729
Order code	523-000098-19
SAP numerator – quantity per pack	1
Numerator – packs per outer box	2
SAP material	912400133376
Net Weight (Piece)	5.510 kg
Commercial Code	523-000098-19
Catalogue number description	eW Burst Powercore gen2, 4000 K, 6° Native (no spread lens), White housing, Architectural

Dimensional drawing



BCP463 G2 19xLED-HB/4000 WH

