



# eW Flex Micro

## eW Flex Micro, 5000 K, Translucent Dome Lens, White Housing, 12 in On-Center Node Spacing

eW Flex Micro, 5000 K, Translucent Dome Lens, White Housing, 12 in On-Center Node Spacing

eW Flex Micro is a versatile strand of small, individually controllable white- light LED nodes. The flexible form factor allows dynamic points of white light to be installed across almost any interior or exterior surface, including walls, ceilings, floors, and three-dimensional sculptures. eW Flex Micro can also be used to light tight alcove spaces and signage.

### Product data

General information		Controls and dimming	
Number of light sources	50 [ 50 pcs]	Dimmable	Yes
Lamp family code	LED-MD [ LED Multi-die]	<b>Mechanical and housing</b>	
Light source colour	Cool white	Housing material	Polycarbonate
Light source replaceable	No	Optic material	Polycarbonate
Driver included	Yes	Colour	White
Optic type	WB [ Wide beam]	<b>Approval and application</b>	
Optical cover/lens type	TSDM12 [ Transparent dome 12 inch separated]	Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]
CE mark	CE mark	Mech. impact protection code	IK09 [ 10 J]
UL mark	UL and cUL mark	<b>Initial performance (IEC compliant)</b>	
<b>Operating and electrical</b>		Init. Corr. Colour Temperature	5000 K
Input Voltage	24 V	Initial input power	25 W

## eW Flex Micro

### Over time performance (IEC compliant)

Lumen Maintenance 70% at 25 °C Calculated	100000
Lumen Maintenance 70% at 25 °C Reported	60000
Lumen Maintenance 70% at 50 °C Calculated	100000
Lumen Maintenance 70% at 50 °C Reported	60000
Lumen Maintenance 80% at 25 °C Calculated	90000
Lumen Maintenance 80% at 25 °C Reported	60000
Lumen Maintenance 80% at 50 °C Calculated	61000
Lumen Maintenance 80% at 50 °C Reported	60000
Lumen Maintenance 90% at 25 °C Calculated	38000
Lumen Maintenance 90% at 25 °C Reported	38000
Lumen Maintenance 90% at 50 °C Calculated	27000
Lumen Maintenance 90% at 50 °C Reported	27000

### Application conditions


Ambient temperature range	-30 to +50 °C
---------------------------	---------------

### Product data

Full product code	871829163951099
Order product name	BGC482 50 5000K TSDM12 WH
EAN/UPC – product	8718291639510
Order code	500-000011-54
SAP numerator – quantity per pack	1
Numerator – packs per outer box	12
SAP material	912400133523
Net Weight (Piece)	1.480 kg
Commercial Code	500-000011-54
Catalogue number description	eW Flex Micro, 5000 K, Translucent Dome Lens, White Housing, 12 in On- Center Node Spacing



### Dimensional drawing



BGC482 50 5000K TSDM12 WH

