



eW Graze MX Powercore

eW Graze MX Powercore, 3000 K, 30° x 60° Beam Angle, 305 mm (1 ft)

eW Graze MX Powercore, 3000 K, 30° x 60° Beam Angle, 305 mm (1 ft)

Many architectural structures need a linear fixture capable of illuminating multiple storeys with minimal setback. Property owners/end users need a controllable product capable of dynamic illumination to draw attention to their establishments and emphasise their brands. Graze MX Powercore is capable of illuminating over 20 meters at very close setback distances. Powercore technology enables simple installation and long product run lengths.

Product data

| General information | |
|-------------------------------|-------------------------------|
| Lamp family code | LED-HB [LED High Brightness] |
| Lamp colour code | White |
| Light source replaceable | No |
| Driver included | Yes |
| Luminaire light beam spread | 30° x 60° |
| Protection class IEC | Safety class I (I) |
| CE mark | CE mark |
| UL mark | UL and cUL mark |
| Lifetime to 50% luminous flux | 60000 h |
| Lifetime to 70% luminous flux | 60000 h |
| | |

| Operating and electrical | |
|-----------------------------|-------------------|
| Input Voltage | 100 to 277 V |
| Input frequency | 50 to 60 Hz |
| | |
| Controls and dimming | |
| Dimmable | Yes |
| | |
| Mechanical and housing | |
| Housing material | Aluminum extruded |
| Optical cover/lens material | Polycarbonate |
| Length | 305 mm |
| | |

eW Graze MX Powercore

| Approval and application | | |
|---|---|--|
| Ingress protection code | IP66 [Dust penetration-protected, jet- | |
| | proof] | |
| Mech. impact protection code | IK10 [20 J vandal-resistant] | |
| Vibration standard | Complies with ANSI C136.31, 3G | |
| Vibration rating | Complies with ANSI C136.31, 3G | |
| | | |
| Initial performance (IEC compliant) | | |
| Lamp colour temperature | 3000 K | |
| Initial input power | 15 W | |
| | | |
| Over time performance (IEC compliant) | | |
| Lumen Maintenance 50% at 25 °C Reported 60000 | | |
| Lumen Maintenance 50% at 50 °C Reported 60000 | | |
| Lumen Maintenance 70% at 25 °C Reported | 60000 | |
| Lumen Maintenance 70% at 50 °C Reported | 60000 | |
| | | |
| Application conditions | | |


-20 to +50 °C

| Product data | |
|-----------------------------------|--|
| Full product code | 871829139461799 |
| Order product name | BCS419 30x60-3000 L305 |
| EAN/UPC – product | 8718291394617 |
| Order code | 523-000080-63 |
| SAP numerator – quantity per pack | 1 |
| Numerator – packs per outer box | 4 |
| SAP material | 912400135116 |
| Net Weight (Piece) | 1.200 kg |
| Commercial Code | 523-000080-63 |
| Catalogue number description | eW Graze MX Powercore, 3000 K, 30° x 60° |
| | Beam Angle, 305 mm (1 ft) |
| | |



Ambient temperature range

Dimensional drawing





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2023, January 10 - data subject to change