



eW Graze QLX Powercore

eW Graze QLX Powercore, 3000 K, 15° x 30° Beam Angle, 305 mm (1 ft)

eW Graze QLX Powercore, 3000 K, 15° x 30° Beam Angle, 305 mm (1 ft)

Many architectural structures need a linear fixture capable of illuminating several storeys with minimal setback and reduced power consumption. Property owners/end users need a controllable product capable of dynamic illumination to draw attention to their establishments and emphasise their brands. Graze QLX Powercore is capable of illuminating over 10 metres at very close setback distances. Powercore technology enables simple installation and long product run lengths.

Product data

General information	
Lamp family code	LED-HB [LED High Brightness]
Light source colour	White
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	PCC [Polycarbonate bowl/cover clear]
Luminaire light beam spread	15° x 30°
Protection class IEC	Safety class I
CE mark	CE mark
UL mark	UL and cUL mark
Operating and electrical	
Input Voltage	100 to 277 V

Input frequency	50 to 60 Hz	
Controls and dimming		
Dimmable	Yes	
Mechanical and housing		
Housing material	Extruded aluminium	
Optical cover/lens material	Polycarbonate	
Length	305 mm	
Colour	Aluminium	

Datasheet, 2023, January 10 data subject to change


eW Graze QLX Powercore

Approval and application	
Ingress protection code	IP66 [Dust penetration-protected, jet-
	proof]
Mech. impact protection code	IK10 [20 J vandal-resistant]
Vibration standard	Complies with ANSI C136.31, 3G
FCC mark	FCC Class A
Vibration rating	Complies with ANSI C136.31, 3G
Initial performance (IEC compliant)	
Init. Corr. Colour Temperature	3000 K
Initial input power	15 W
Over time performance (IEC complia	int)
Lumen Maintenance 50% at 25 °C	60000
Reported	
Lumen Maintenance 50% at 50 °C	60000
Reported	
Lumen Maintenance 70% at 25 °C	60000
Reported	
Lumen Maintenance 70% at 50 °C	60000
Reported	

Application conditions	
Ambient temperature range	-40 to +50 °C
Product data	
Full product code	871869921018299
Order product name	BCS427 15x30-3000 L305
EAN/UPC - product	8718699210182
Order code	523-000081-62
SAP numerator – quantity per pack	1
Numerator – packs per outer box	4
SAP material	912400135248
Net Weight (Piece)	1.103 kg
Commercial Code	523-000081-62
Catalogue number description	eW Graze QLX Powercore, 3000 K, 15° x 30°
	Beam Angle, 305 mm (1 ft)



Dimensional drawing



BCS427 15x30-3000 L305



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.