



# eW Graze QLX Powercore

### BCS427 60x30-3500 L609

eW Graze QLX Powercore, 3500 K, 60° x 30° Beam Angle, 610 mm (2 ft)

Many architectural structures need a linear fixture capable of illuminating several storeys with minimal setback and reduced power consumption. Property owners/end users need a controllable product capable of dynamic illumination to draw attention to their establishments and emphasise their brands. Graze QLX Powercore is capable of illuminating over 10 metres at very close setback distances. Powercore technology enables simple installation and long product run lengths.

#### **Product data**

General Information	
Lamp family code	LED-HB [ LED High Brightness]
Lamp colour code	White
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	PCC [ Polycarbonate bowl/cover clear]
Luminaire light beam spread	60° x 30°
Protection class IEC	Safety class I (I)
CE mark	CE mark
UL mark	UL and cUL mark
Lifetime to 70% luminous flux	100000 h
Operating and Electrical	
Input Voltage	100 to 277 V

Input frequency	50 to 60 Hz
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Housing material	Aluminum extruded
Optical cover/lens material	Polycarbonate
Length	609 mm
Colour	Aluminium
Approval and Application	
Ingress protection code	IP66 [ Dust penetration-protected, jet-
	proof]
Mech. impact protection code	IK10 [ 20 J vandal-resistant]

#### eW Graze QLX Powercore

Complies with ANSI C136.31, 3G	
Complies with ANSI C136.31, 3G	
t)	
3500 K	
10 W	
Over Time Performance (IEC Compliant)	
60000	
60000	
60000	
60000	


-40 to +50 °C

Product Data	
Full product code	871869921065699
Order product name	BCS427 60x30-3500 L609
EAN/UPC – product	8718699210656
Order code	523-000081-89
SAP numerator - quantity per pack	1
Numerator – packs per outer box	4
SAP material	912400135295
SAP net weight (piece)	2.700 kg
Commercial Code	523-000081-89
Catalogue number description	eW Graze QLX Powercore, 3500 K, 60° x 30°
	Beam Angle, 610 mm (2 ft)



## Dimensional drawing

Ambient temperature range





© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2022, February 21 - data subject to change