



eW Graze QLX Powercore

BCS427 10x60-3500 L1219

eW Graze QLX Powercore, 3500 K, 15° x 30° Beam Angle, 1219 mm (4 ft)

Many architectural structures need a linear fixture capable of illuminating several storeys with minimal setback and reduced power consumption. Property owners/end users need a controllable product capable of dynamic illumination to draw attention to their establishments and emphasise their brands. Graze QLX Powercore is capable of illuminating over 10 metres at very close setback distances. Powercore technology enables simple installation and long product run lengths.

Product data

General Information		Controls and Dimming	
Lamp family code	LED-HB [LED High Brightness]	Dimmable	Yes
Lamp colour code	White		
Light source replaceable	No	Mechanical and Housing	
Driver included	Yes	Housing material	Aluminum extruded
Optical cover/lens type	PCC [Polycarbonate bowl/cover clear]	Optical cover/lens material	Polycarbonate
Luminaire light beam spread	10° x 60°	Length	1219 mm
Protection class IEC	Safety class I (I)	Colour	Aluminium
CE mark	CE mark		
UL mark	UL and cUL mark	Approval and Application	
Operating and Electrical		Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Input Voltage	100 to 277 V	Mech. impact protection code	IK10 [20 J vandal-resistant]
Input frequency	50 to 60 Hz	Vibration standard	Not compliant to ANSI C136.31, 3G. Special orders are available to conform to the standard.

eW Graze QLX Powercore

	Please contact your Color Kinetics Lighting Sales rep for custom configurations.
Vibration rating	Not compliant to ANSI C136.31, 3G. Special orders are available to conform to the standard. Please contact your Color Kinetics Lighting Sales rep for custom configurations.

Initial Performance (IEC Compliant)

Lamp colour temperature	3500 K
Initial input power	20 W

Over Time Performance (IEC Compliant)

Lumen Maintenance 50% at 25 °C Reported	60000
Lumen Maintenance 50% at 50 °C Reported	60000
Lumen Maintenance 70% at 25 °C Reported	60000
Lumen Maintenance 70% at 50 °C Reported	60000

Application Conditions	
Ambient temperature range	-40 to +50 °C
Product Data	
Full product code	871869921072400
Order product name	BCS427 10x60-3500 L1219
EAN/UPC – product	8718699210724
Order code	523-000081-97
SAP numerator – quantity per pack	1
Numerator – packs per outer box	1
SAP material	912400135303
SAP net weight (piece)	4.700 kg
Commercial Code	523-000081-97
Catalogue number description	eW Graze QLX Powercore, 3500 K, 15° x 30° Beam Angle, 1219 mm (4 ft)



Dimensional drawing

