

Vaya Cove LP G2

Vaya Cove LP G2, 4000 K, 1219 mm (4 ft), UL/CE

Vaya Cove LP G2, 4000 K, 1219 mm (4 ft), UL/CE

Vaya Cove LP G2 is a reliable cost-effective LED luminaire offering crisp white light for interior use. Designed for linear cove and accent lighting applications this luminaire offers a very low profile and integrated connectors to eliminate socket shadows. Vaya Cove LP offers on/off control or dimming via the use of any standard 0-10 V or DALI dimming controller.

Product data

General information	
Lamp family code	LED-HB [LED High Brightness]
Beam angle of light source	110 °
Light source colour	Cool white
Light source replaceable	No
Driver included	No
Luminaire light beam spread	110°
CE mark	CE mark
UL mark	UL and cUL mark

Operating and electrical	
Input Voltage	24 V
Control signal voltage	1-10 V DC

Controls and dimming	
Dimmable	Yes

Mechanical and housing	
Housing material	Polycarbonate
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Optical cover/lens finish	Clear
Length	1200 mm
Colour	White

Approval and application	
Ingress protection code	IP40 [Wire-protected]

Initial performance (IEC compliant)	
Initial luminous flux (system flux)	1116 lm
Initial luminous flux at colour temperature of 4,000 K	1116 lm
Initial LED luminaire efficacy	106 lm/W
Init. Corr. Colour Temperature	4000 K
Init. Colour rendering index	≥80
Initial input power	10.6 W

Over time performance (IEC compliant)	
Lumen Maintenance 70% at 25 °C Calculated	100000
Lumen Maintenance 70% at 25 °C Reported	60000

Vaya Cove LP G2

Lumen Maintenance 70% at 50 °C Calculated	100000
Lumen Maintenance 70% at 50 °C Reported	60000
Lumen Maintenance 80% at 25 °C Calculated	100000
Lumen Maintenance 80% at 25 °C Reported	60000
Lumen Maintenance 80% at 50 °C Calculated	97000
Lumen Maintenance 80% at 50 °C Reported	60000
Lumen Maintenance 90% at 25 °C Calculated	56000
Lumen Maintenance 90% at 25 °C Reported	56000
Lumen Maintenance 90% at 50 °C Calculated	45000
Lumen Maintenance 90% at 50 °C Reported	45000


Order product name	SM452L 4000 24V L1200 CE UL
EAN/UPC – product	8718699213046
Order code	350-000017-11
SAP numerator – quantity per pack	1
Numerator – packs per outer box	30
SAP material	912400135346
Net Weight (Piece)	0.330 kg
Commercial Code	350-000017-11
Catalogue number description	Vaya Cove LP G2, 4000 K, 1219 mm (4 ft), UL/CE

Application conditions	
Ambient temperature range	-20 to +50 °C

IP 40

Product data	
Full product code	871869921304699

Dimensional drawing



SM452L 4000 24V L1200 CE UL

© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.