



eW Burst Powercore gen2

eW Burst Powercore gen2, 3000 K, 6° Native (no spread lens), Gray housing, Landscape

eW Burst Powercore gen2, 3000 K, 6° Native (no spread lens), Gray housing, Landscape

eW Burst Powercore gen2 is a high-output, exterior-rated LED lighting luminaire designed for accent and site lighting. Architectural and Landscape versions deliver high-quality white light output in 2700 K, 3000 K, 3500 K, and 4000 K to support a range of uplighting, floodlighting, and decorative lighting applications.

Product data

General information		
Light source replaceable	No	
Luminaire light beam spread	6°	
CE mark	CE mark	
UL mark	UL and cUL mark	
Operating and electrical		
Input Voltage	100 to 277 V	
Input Frequency	50 to 60 Hz	
Mechanical and housing		
Color	Gray	

Approval and application	
Ingress protection code	IP66 [Dust penetration-protected, jet-
	proof]
Corrosion Resistance	Complies with ASTM B117 standard for >
	1,500 hours
FCC mark	FCC Class A
Initial performance (IEC complia	ant)
Initial LED luminaire efficacy	66 lm/W
Init. Corr. Color Temperature	3000 K
Init. Color Rendering Index	83
Initial input power	30 W
Over time performance (IEC cor	npliant)
Lumen Maintenance 50% at 25°C Cal	culated 100000

Datasheet, 2022, October 11 data subject to change

eW Burst Powercore gen2

Lumen Maintenance 50% at 25°C Reported	51000
Lumen Maintenance 50% at 50°C Calculated	100000
Lumen Maintenance 50% at 50°C Reported	51000
Lumen Maintenance 70% at 25°C Calculated	84000
Lumen Maintenance 70% at 25°C Reported	51000
Lumen Maintenance 70% at 50°C Calculated	83000
Lumen Maintenance 70% at 50°C Reported	51000
Lumen Maintenance 90% at 25°C Calculated	28000
Lumen Maintenance 90% at 25°C Reported	28000
Lumen Maintenance 90% at 50°C Calculated	27000
Lumen Maintenance 90% at 50°C Reported	27000

Order product name	BCP463 G2 19xLED-HB/3000 HMA GR
EAN/UPC - Product	8718699215750
Order code	523-000098-24
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2
Material Nr. (12NC)	912400135372
Net Weight (Piece)	3.470 kg
Catalog Number	523-000098-24
Catalog Number Description	eW Burst Powercore gen2, 3000 K, 6°
	Native (no spread lens), Gray housing,
	Landscape




Application conditions

Ambient temperature range -40 to +50 °C

Product data

Full product code 871869921575099

Dimensional drawing



BCP463 G2 19xLED-HB/3000 HMA GR



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.