**PHILIPS** Lighting



# eW Burst Powercore gen2

# eW Burst Powercore gen2, 3000 K, 6° Native (no spread lens), White housing, Landscape

eW Burst Powercore gen2, 3000 K, 6° Native (no spread lens), White housing, Landscape

eW Burst Powercore gen2 is a high-output, exterior-rated LED lighting luminaire designed for accent and site lighting. Architectural and Landscape versions deliver high-quality white light output in 2700 K, 3000 K, 3500 K, and 4000 K to support a range of uplighting, floodlighting, and decorative lighting applications.

### **Product data**

No	
6°	
CE mark	
UL and cUL mark	
100 to 277 V	
50 to 60 Hz	
White	
	6° CE mark UL and cUL mark 100 to 277 V 50 to 60 Hz

Approval and application		
Ingress protection code	IP66 [ Dust penetration-protected, jet-	
	proof]	
Corrosion Resistance	Complies with ASTM B117 standard for >	
	1,500 hours	
FCC mark	FCC Class A	
Initial performance (IEC compliant)		
Initial LED luminaire efficacy	66 lm/W	
Init. Corr. Color Temperature	3000 K	
Init. Color Rendering Index	83	
Initial input power	30 W	
Over time performance (IEC compliant)		
Lumen Maintenance 50% at 25°C Calculated 100000		

### eW Burst Powercore gen2

Lumen Maintenance 50% at 25°C Reported	51000
Lumen Maintenance 50% at 50°C Calculated	100000
Lumen Maintenance 50% at 50°C Reported	51000
Lumen Maintenance 70% at 25°C Calculated	84000
Lumen Maintenance 70% at 25°C Reported	51000
Lumen Maintenance 70% at 50°C Calculated	83000
Lumen Maintenance 70% at 50°C Reported	51000
Lumen Maintenance 90% at 25°C Calculated	28000
Lumen Maintenance 90% at 25°C Reported	28000
Lumen Maintenance 90% at 50°C Calculated	27000
Lumen Maintenance 90% at 50°C Reported	27000
Application conditions	

-40 to +50 °C

871869921579899


BCP463 G2 19xLED-HB/3000 HMA WH
8718699215798
523-000098-30
1
2
912400135378
3.470 kg
523-000098-30
eW Burst Powercore gen2, 3000 K, 6°
Native (no spread lens), White housing,
Landscape

Ambient temperature range

#### Product data

Full product code

**Dimensional drawing** 



BCP463 G2 19xLED-HB/3000 HMA WH



IP 66

© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2022, October 11 - data subject to change