
PHILIPS

Lighting



eW Flex Compact

eW Flex Compact, 2700 K, Narrow Beam Lens, White Housing, 4 in on-center node spacing

eW Flex Compact, 2700 K, Narrow Beam Lens, White Housing, 4 in on-center node spacing

eW Flex Compact is a versatile strand of large, individually controllable white-light LED nodes. The flexible form factor allows dynamic points of white light to be installed across almost any interior or exterior surface, including walls, ceilings, floors, and three-dimensional sculptures. eW Flex Compact can also be used to light tight alcove spaces and signage.

Product data

General information	
Lamp family code	LED-MD [LED Multi-die]
Light source replaceable	No
Driver included	No
Optical cover/lens type	PC-UV [Polycarbonate bowl/cover UV-resistant]
CE mark	CE mark
UL mark	UL mark

Light technical	
Luminance per node	122240 cd/m²
Luminous intensity (peak value) on beam axis per node	85.5 cd

Operating and electrical	
Input Voltage	24 V

Controls and dimming	
Dimmable	Yes

Mechanical and housing	
Housing material	Polycarbonate
Optic material	Polycarbonate
Colour	White

Approval and application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK10 [20 J vandal-resistant]
FCC mark	FCC Class A

Initial performance (IEC compliant)	
Initial luminous flux at colour temperature of 2,700 K	73 lm

eW Flex Compact

Init. Corr. Colour Temperature	2700 K
Initial input power	1 W

Over time performance (IEC compliant)

Lumen Maintenance 70% at 25 °C Calculated	56000
Lumen Maintenance 70% at 25 °C Reported	56000
Lumen Maintenance 70% at 50 °C Calculated	56000
Lumen Maintenance 70% at 50 °C Reported	56000
Lumen Maintenance 80% at 25 °C Calculated	37000
Lumen Maintenance 80% at 25 °C Reported	37000
Lumen Maintenance 80% at 50 °C Calculated	37000
Lumen Maintenance 80% at 50 °C Reported	37000
Lumen Maintenance 90% at 25 °C Calculated	20000
Lumen Maintenance 90% at 25 °C Reported	20000
Lumen Maintenance 90% at 50 °C Calculated	20000
Lumen Maintenance 90% at 50 °C Reported	20000

Application conditions

Ambient temperature range	-40 to +50 °C

Product data

Full product code	871869921405099
Order product name	BGC481 50 2700K NRRW WH P102
EAN/UPC – product	8718699214050
Order code	500-000012-56
SAP numerator – quantity per pack	1
Numerator – packs per outer box	6
SAP material	912400135782
Net Weight (Piece)	1.740 kg
Commercial Code	500-000012-56
Catalogue number description	eW Flex Compact, 2700 K, Narrow Beam Lens, White Housing, 4 in on-center node spacing



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.