



## eW Flex Compact

eW Flex Compact, 6500 K, Narrow Beam Lens, White Housing, 12 in on-center node spacing

eW Flex Compact, 6500 K, Narrow Beam Lens, White Housing, 12 in on-center node spacing

eW Flex Compact is a versatile strand of large, individually controllable white-light LED nodes. The flexible form factor allows dynamic points of white light to be installed across almost any interior or exterior surface, including walls, ceilings, floors, and three-dimensional sculptures. eW Flex Compact can also be used to light tight alcove spaces and signage.

## **Product data**

General Information	
Lamp family code	LED-MD [ LED Multi-die]
Light source replaceable	No
Driver included	No
Optical cover/lens type	PC-UV [ Polycarbonate bowl/cover UV-
	resistant]
CE mark	CE mark
UL mark	UL mark
Operating and Electrical	
Input Voltage	24 V
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Housing material	Polycarbonate

Optic material	Polycarbonate	
Colour	White	
Approval and Application		
Ingress protection code	IP66 [ Dust penetration-protected, jet-	
	proof]	
Mech. impact protection code	IK10 [ 20 J vandal-resistant]	
Initial Performance (IEC Compliant)		
Lamp colour temperature	6500 K	
Initial input power	1 W	
Over Time Performance (IEC Compliant)		
Lumen Maintenance 70% at 25 °C Calculated	56000	
Lumen Maintenance 70% at 25 °C Reported	56000	
Lumen Maintenance 70% at 50 °C Calculated 56000		
Lumen Maintenance 70% at 50 °C Reported	56000	

Datasheet, 2021, September 13 data subject to change

## **eW Flex Compact**

Lumen Maintenance 80% at 25 °C Calculated	37000	
Lumen Maintenance 80% at 25 °C Reported	37000	
Lumen Maintenance 80% at 50 °C Calculated	37000	
Lumen Maintenance 80% at 50 °C Reported	37000	
Lumen Maintenance 90% at 25 °C Calculated	20000	
Lumen Maintenance 90% at 25 °C Reported	20000	
Lumen Maintenance 90% at 50 °C Calculated 20000		
Lumen Maintenance 90% at 50 °C Reported	20000	
Application Conditions		
Ambient temperature range	-40 to +50 °C	
Product Data		


871869921431999

Order product name	BGC481 50 6500K NRRW WH P305
EAN/UPC – product	8718699214319
Order code	500-000012-86
SAP numerator – quantity per pack	1
Numerator – packs per outer box	6
SAP material	912400135813
SAP net weight (piece)	1.740 kg
Commercial Code	500-000012-86
Catalogue number description	eW Flex Compact, 6500 K, Narrow Beam
	Lens, White Housing, 12 in on-center node
	spacing



## Dimensional drawing

Full product code



eW Flex Compact



© 2021 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.