



LytePro 32 LED Wall Sconce

LED, 6913 lumens, 71W, 700mA, 4000K, 120-277V, Textured White

LED, 6913 lumens, 71W, 700mA, 4000K, 120-277V, Textured White - 98 lm/W

The Lytepro 32 Series Architectural Wall Sconce from KEENE incorporates modern styling, high performance, and energy efficient LEDs. Featuring Philips LedGine platform for future proof designs that enhance upgrades and simplify replacements. Ideal LED solution to replace 150 watt and 175 watt HID sources with up to 60% energy savings.

Product data

General Information	
Lamp Source Code	LED
Colour Temperature	4000K
CRI	70
Photometric Distribution Type	Type III
Mounting	Wall
B.U.G. Rating	B2U0G2
Awards	DLC QPL
Operating and Electrical	
Voltages	120/208/240/277 V
Luminaire Input Watts	71

Approval and Application	
Safety Listing	ETL
DesignLights Consortium Qualified Product List	DesignLights Consortium Qualified Product List
Initial Performance (IEC Compliant)	
Luminaire Lumens	6900
Efficacy	98 lm/W
Application Conditions	
Max Ambient Temp	+40 °C
Min Ambient Temp	-40 °C

LytePro 32 LED Wall Sconce

Product Data

Order product name	LPW32-78WH
EAN/UPC - Product	190096011315
Order code	LPW32-78WH
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	3
Material Nr. (12NC)	912400531035

Net Weight (Piece)	0.001 kg
Catalog Number	LPW32-78WH
Catalog Number Description	LED, 6913 lumens, 71W, 700mA, 4000K, 120-277V, Textured White

