



FBX LED High Bay

20,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution

20,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution - 138 lm/W

The FBX LED High Bay is a compact and economical luminaire utilizing the latest in LED technology. With several lumen packages and optical distribution patterns available, the FBX offers exceptional lighting in mid to high ceiling applications. Save energy without straining your project budget or sacrificing your light output.

Product data

General Information	
Colour Temperature	4000 K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended
Operating and Electrical	
Voltages	120/208/240/277/347/480/UNIV V
Luminaire Input Watts	142
Initial Performance (IEC Compliant)	
Luminaire Lumens	20000
Efficacy	138 lm/W

Product Data	
Order product name	FBX20LL40-UNV
EAN/UPC - Product	781370299668
Order code	FBX20LL40-UNV
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912401261321
Net Weight (Piece)	11.335 kg
Catalog Number	FBX20LL40-UNV
Catalog Number Description	20,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution