



# FBX LED High Bay

**45,000 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution**

45,000 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution - 146 lm/W

The FBX LED High Bay is a compact and economical luminaire utilizing the latest in LED technology. With several lumen packages and optical distribution patterns available, the FBX offers exceptional lighting in mid to high ceiling applications. Save energy without straining your project budget or sacrificing your light output.

## Product data

General Information	
Colour Temperature	4000 K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended
Operating and Electrical	
Voltages	120/208/240/277/347/480/UNIV V
Luminaire Input Watts	315
Initial Performance (IEC Compliant)	
Luminaire Lumens	45000
Efficacy	146 lm/W

Product Data	
Order product name	FBX45LL40-UNV
EAN/UPC - Product	781370528249
Order code	FBX45LL40-UNV-M
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912401262642
Net Weight (Piece)	0.001 kg
Catalog Number	FBX45LL40-UNV-M
Catalog Number Description	45,000 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution