



## **FBX LED High Bay**

## 12,000 Nominal Delivered Lumens, 4000K, 80 CRI, Narrow Distribution, Frosted Acrylic Lens

12,000 Nominal Delivered Lumens, 4000K, 80 CRI, Narrow Distribution, Frosted Acrylic Lens - 123 lm/W

The FBX LED High Bay is a compact and economical luminaire utilizing the latest in LED technology. With several lumen packages and optical distribution patterns available, the FBX offers exceptional lighting in mid to high ceiling applications. Save energy without straining your project budget or sacrificing your light output.

## **Product data**

General Information	
Colour Temperature	4000 K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended
Operating and Electrical	
Voltages	120/208/240/277/347/480/UNIV V
Luminaire Input Watts	88
Initial Performance (IEC Compliant)	
Luminaire Lumens	12000
Efficacy	123 lm/W

Product Data	
Order product name	FBX12LL40-UNV
EAN/UPC - Product	781370564995
Order code	FBX12LL40-UNV-N-LFA
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box 1	
Material Nr. (12NC)	912401263044
Net Weight (Piece)	0.001 kg
Catalog Number	FBX12LL40-UNV-N-LFA
Catalog Number Description	12,000 Nominal Delivered Lumens, 4000K, 80 CRI,
	Narrow Distribution, Frosted Acrylic Lens