



## SofTrace Surface LED

## 2SST34L835-2-DS-UNV

2x2, Surface, 3400 Nominal Delivered Lumens, 80 CRI, 3500K, Diffuse-Smooth

SofTrace Surface LED brings new meaning to the concept of combining style with performance. Equipped with a fresh streamlined design and innovative technology, SofTrace provides a huge step forward for the lighting industry. The sleek profile design belies the true "horsepower under the hood". With efficiency levels exceeding 95% and lumens per Watt as great as 87, an architectural product now delivers leading edge performance for the most environmentally conscious user.

## **Product data**

General Information		
Lamp Source Code	LED	
Color Temperature	3500K	
CRI	80	
Photometric Distribution Type	Direct	
Mounting	Surface	
Operating and Electrical		
Voltages	120/277/347 V	
Luminaire Input Watts	41	
Mechanical and Housing		
Fixture Size	2 ft x 2 ft	
Shape	Square	
Initial Performance (IEC Compliant)		
Luminaire Lumens	3400	

Product Data	
Order product name	2SST34L835-2-DS-UNV
EAN/UPC - Product	781370212278
Order code	912401266122
Local order code	7021227
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box 1	
Material Nr. (12NC)	912401266122
Net Weight (Piece)	0.001 kg
Commercial Code	2SST34L835-2-DS-UNV-DIM
Catalog Number Description	2x2, Surface, 3400 Nominal Delivered Lumens, 80 CRI,
	3500K, Diffuse-Smooth
Quick Ship	-

Datasheet, 2018, July 24 data subject to change

## SofTrace Surface LED

